according to Regulation (EC) No 1907/2006

| ADDINOL Chain Lub | e XHT 150 |
|-------------------|-----------|
|-------------------|-----------|

Revision date: 27.08.2024

Product code: 766023

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

ADDINOL Chain Lube XHT 150

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant and additive.

## 1.3. Details of the supplier of the safety data sheet

| Manufacturer |
|--------------|
|--------------|

| wanufacturer             |  |                              |
|--------------------------|--|------------------------------|
| Company name:            | ADDINOL Lube Oil GmbH                  |                              |
|                          | Gebäude 4609                           |                              |
| Street:                  | Am Haupttor                            |                              |
| Place:                   | D-06237 Leuna                          |                              |
| Telephone:               | +49 (0) 3461 845-0                     | Telefax:+49 (0) 3461 845-555 |
| E-mail:                  | info@addinol.de                        |                              |
| Contact person:          | Application Technology                 |                              |
| Internet:                | www.addinol.de                         |                              |
| Responsible Department:  | ADDINOL Application Technology         |                              |
| Supplier                 |  |                              |
| Company name:            | GEM OILS LIMITED                       |                              |
| Place:                   | IRL-H12K298 Regaskin Co. Cavan         |                              |
| Telephone:               | +353 49 4378116                        | Telefax: +353 49 4368329     |
| E-mail:                  | sales@gemoils.ie                       |                              |
| Contact person:          | GEM OILS LIMITED                       | Telephone: +353 49 4378116   |
| E-mail:                  | sales@gemoils.ie                       |                              |
| Internet:                | https://gemoils.ie/                    |                              |
| 1.4. Emergency telephone | Healthcare Professionals: +353 (1) 809 | 2566 (24 hour service)       |
| numbori                  |  |                              |

number:

SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

# This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

## 2.2. Label elements

### Regulation (EC) No 1272/2008

## Pictograms:



## Hazard statements

H411

Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

| countionaly. | statements  |
|--------------|---|
| P273         | Avoid release to the environment.                         |
| P391         | Collect spillage.   |
| P501         | Dispose of contents/container to a waste disposal system. |

according to Regulation (EC) No 1907/2006

### **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 2 of 13

## Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Spilled product must not leak into the ground. Do not allow uncontrolled leakage of product into the environment.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Mixture of synthetic base components and additives.

#### **Relevant ingredients**

| CAS No     | Chemical name                      |                         |                  |             |  |
|------------|------------------------------------|-------------------------|------------------|-------------|--|
|            | EC No                              | Index No                | REACH No         |             |  |
|            | Classification (Regulation (EC) No | 1272/2008)              |                  |             |  |
| 9003-29-6  | Polybutenes                        |                         |                  | 10 - < 20 % |  |
|            | 500-004-7                          |                         |                  |             |  |
|            | Asp. Tox. 1; H304                  |                         |                  |             |  |
| 68937-41-7 | Triaryl phosphate isopropylated    |                         |                  | 1 - < 2.5 % |  |
|            | 273-066-3                          |                         | 01-2119535109-41 |             |  |
|            | Repr. 2, STOT RE 2, Aquatic Chro   | nic 1; H361fd H373 H410 |                  |             |  |
| 68442-68-2 | Styrenated N-phenyl-benzenamine    |                         |                  | 1 - < 2.5 % |  |
|            | 270-485-3                          |                         | 01-2120115789-46 |             |  |
|            | Aquatic Chronic 4; H413            |                         |                  |             |  |

## Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

| CAS No     | EC No   | Chemical name                             | Quantity    |  |
|------------|---|---|-------------|--|
|            | Specific Conc. Limits, M-factors and ATE  |   |             |  |
| 9003-29-6  | 500-004-7   | Polybutenes                               | 10 - < 20 % |  |
|            | inhalation: LC50 = 4820 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 mg/kg |   |             |  |
| 68937-41-7 | 273-066-3   | Triaryl phosphate isopropylated           |             |  |
|            | dermal: LD50 = > 10000 mg/kg Aquatic Chronic 1; H410: M=10                                      |   |             |  |
| 68442-68-2 | 270-485-3   | Styrenated N-phenyl-benzenamine           |             |  |
|            | dermal: LD50 =  | = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg |             |  |

#### **Further Information**

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 3 of 13

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Sulphur oxides. Nitrogen oxides (NOx). Phosphorus oxides. carbon black.

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing. Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

## 6.3. Methods and material for containment and cleaning up

### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8

according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 4 of 13

## Section 12: Ecological Information (non-mandatory) Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

## Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Provide adequate ventilation as well as local exhaustion at critical locations. Keep/Store only in original container. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Oxidizing agent

#### Further information on storage conditions

Protect against: UV-radiation/sunlight. Frost. heat. Recommended storage temperature: 5 - 40°C

#### 7.3. Specific end use(s)

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Occupational exposure limits

| CAS No   | Substance     | ppm | mg/m³ | fib/cm³ | Category      | Origin |
|----------|---------------|-----|-------|---------|---------------|--------|
| 122-39-4 | Diphenylamine | -   | 10    |         | TWA (8 h)     |        |
|          |               | -   | 20    |         | STEL (15 min) |        |

according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 5 of 13

## **DNEL/DMEL** values

| CAS No      | Substance                       |                |          |                         |  |
|-------------|---------------------------------|----------------|----------|-------------------------|--|
| DNEL type   |                                 | Exposure route | Effect   | Value                   |  |
| 68937-41-7  | Triaryl phosphate isopropylated |                |          |                         |  |
| Consumer DN | NEL, acute                      | oral           | systemic | 50 mg/kg bw/day         |  |
| Worker DNEL | ., long-term                    | inhalation     | systemic | 0,145 mg/m³             |  |
| Worker DNEL | ., acute                        | inhalation     | systemic | 700 mg/m <sup>3</sup>   |  |
| Worker DNEL | ., long-term                    | dermal         | systemic | 0,25 mg/kg<br>bw/day    |  |
| Worker DNEL | ., acute                        | dermal         | systemic | 2000 mg/kg<br>bw/day    |  |
| Worker DNEL | ., acute                        | dermal         | local    | 16 mg/cm <sup>2</sup>   |  |
| Consumer DN | NEL, acute                      | inhalation     | systemic | 350 mg/m <sup>3</sup>   |  |
| Consumer DN | NEL, long-term                  | dermal         | systemic | 0,0298 mg/kg<br>bw/day  |  |
| Consumer DN | NEL, acute                      | dermal         | systemic | 100 mg/kg bw/day        |  |
| Consumer DN | NEL, acute                      | dermal         | local    | 8 mg/cm <sup>2</sup>    |  |
| Consumer DN | NEL, long-term                  | oral           | systemic | 0,00835 mg/kg<br>bw/day |  |
| 68442-68-2  | Styrenated N-phenyl-benzenamine |                |          |                         |  |
| Worker DNEL | ., long-term                    | inhalation     | systemic | 16,4 mg/m <sup>3</sup>  |  |
| Worker DNEL | ., long-term                    | dermal         | systemic | 2,33 mg/kg<br>bw/day    |  |
| Consumer DN | NEL, long-term                  | inhalation     | systemic | 2,9 mg/m³               |  |
| Consumer DN | NEL, long-term                  | dermal         | systemic | 0,833 mg/kg<br>bw/day   |  |
| Consumer DN | NEL, long-term                  | oral           | systemic | 0,167 mg/kg<br>bw/day   |  |

### **PNEC** values

| CAS No  | Substance                                     |            |  |  |
|---|---|------------|--|--|
| Environmental compartment Value                     |   |            |  |  |
| 68937-41-7  | Triaryl phosphate isopropylated               |            |  |  |
| Freshwater  |   | 0 mg/l     |  |  |
| Freshwater (i                                       | Freshwater (intermittent releases) 0,015 mg/l |            |  |  |
| Marine water  | ne water 0 mg/l                               |            |  |  |
| Freshwater sediment 0,185 mg/kg                     |   |            |  |  |
| Marine sediment 0,018 mg/kg                         |   |            |  |  |
| Secondary poisoning 1                               |   | 1,85 mg/kg |  |  |
| Micro-organisms in sewage treatment plants (STP) 10 |   |            |  |  |
| Soil  | 2,5 mg/kg                                     |            |  |  |

## Additional advice on limit values

Recommended limit value for oil mist TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

### 8.2. Exposure controls

according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 6 of 13





#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

| Physical state:<br>Colour:<br>Odour:<br>Odour threshold: | liquid<br>yellow - brown<br>characteristic<br>not determined |                     |                 |
|--|--|---------------------|-----------------|
|  |  |                     | Test method     |
| Melting point/freezing point:                            |  | No data available   |                 |
| Boiling point or initial boiling point and               |  | not determined      |                 |
| boiling range:   |  |                     |                 |
| Flammability:  |  | No data available   |                 |
| Lower explosion limits:                                  |  | No data available   |                 |
| Upper explosion limits:                                  |  | No data available   |                 |
| Flash point:   |  | 280 °C              | DIN EN ISO 2592 |
| Auto-ignition temperature:                               |  | not determined      | DIN 51794       |
| Decomposition temperature:                               |  | No data available   |                 |
| pH-Value:  |  | not applicable      |                 |
| Viscosity / kinematic:<br>(at 40 °C)                     |  | 145 mm²/s           | DIN 51562       |
| Water solubility:  |  | virtually insoluble |                 |
| Solubility in other solvents                             |  |                     |                 |
| No data available  |  |                     |                 |

according to Regulation (EC) No 1907/2006

| ADDINOL Chain Lube XHT 150                       |                         |              |  |  |  |
|--|-------------------------|--------------|--|--|--|
| Revision date: 27.08.2024                        | Product code: 766023    | Page 7 of 13 |  |  |  |
| Partition coefficient n-octanol/water:           | No data available       |              |  |  |  |
| Vapour pressure:                                 | No data available       |              |  |  |  |
| Density (at 15 °C):                              | 0,950 g/cm <sup>3</sup> | DIN 51757    |  |  |  |
| Relative vapour density:                         | No data available       |              |  |  |  |
| Particle characteristics:                        | No data available       |              |  |  |  |
| 9.2. Other information                           |                         |              |  |  |  |
| Information with regard to physical hazard class | es                      |              |  |  |  |
| Explosive properties                             |                         |              |  |  |  |
| No data available                                |                         |              |  |  |  |
| Self-ignition temperature                        |                         |              |  |  |  |
| Solid:   | No data available       |              |  |  |  |
| Gas:   | No data available       |              |  |  |  |
| Oxidizing properties                             |                         |              |  |  |  |
| No data available                                |                         |              |  |  |  |
| Other safety characteristics                     |                         |              |  |  |  |
| Evaporation rate:                                | No data available       |              |  |  |  |
| Pour point:                                      | -48 °C                  | ASTM D 7346  |  |  |  |

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

## 10.3. Possibility of hazardous reactions

No known hazardous reactions.

## 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

#### 10.5. Incompatible materials

Reacts with : Oxidising agent, strong. Acid.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Sulphur oxides. Nitrogen oxides (NOx). Phosphorus oxides. carbon black.

#### **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Acute toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

## ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

## according to Regulation (EC) No 1907/2006

## ADDINOL Chain Lube XHT 150

Revision date: 27.08.2024

Product code: 766023

Page 8 of 13

| CAS No     | Chemical name            |               |           |         |                     |                           |
|------------|--------------------------|---------------|-----------|---------|---------------------|---------------------------|
|            | Exposure route           | Dose          |           | Species | Source              | Method                    |
| 9003-29-6  | Polybutenes              | Polybutenes   |           |         |                     |                           |
|            | oral                     | LD50<br>mg/kg | > 10000   | Rat     | Study report (1986) | OECD Guideline 401        |
|            | dermal                   | LD50<br>mg/kg | > 2000    | Rat     | Study report (1996) | OECD Guideline 402        |
|            | inhalation (4 h) vapour  | LC50          | 4820 mg/l | Rat     |                     |                           |
| 68937-41-7 | Triaryl phosphate isopro | pylated       |           | -       | _                   |                           |
|            | dermal                   | LD50<br>mg/kg | > 10000   | Rabbit  | Study report (1976) | other: 16 CFR 1500.<br>40 |
| 68442-68-2 | Styrenated N-phenyl-ber  | nzenamine     |           |         |                     |                           |
|            | oral                     | LD50<br>mg/kg | > 5000    | Rat     | Study report (1976) | OECD Guideline 401        |
|            | dermal                   | LD50<br>mg/kg | > 2000    | Rat     | Study report (2016) | OECD Guideline 402        |

### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

## Endocrine disrupting properties

not applicable

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Toxic to aquatic life with long lasting effects. Mixture not tested.

## according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 9 of 13

| CAS No     | Chemical name                   |                |          |           |                               |                                       |  |
|------------|---------------------------------|----------------|----------|-----------|-------------------------------|---------------------------------------|--|
|            | Aquatic toxicity                | Dose           |          | [h]   [d] | Species                       | Source                                | Method                                   |
| 9003-29-6  | Polybutenes                     |                |          |           |                               |                                       |  |
|            | Acute fish toxicity             | LL50<br>mg/l   | > 1000   | 96 h      | Oncorhynchus mykiss           | REACh<br>Registration<br>Dossier      | other: REACH<br>Guidance on<br>QSARs R.6 |
|            | Acute algae toxicity            | ErC50<br>mg/l  | > 1000   | 72 h      | Raphidocelis<br>subcapitata   | REACh<br>Registration<br>Dossier      | other: REACH<br>Guidance on<br>QSARs R.6 |
|            | Acute crustacea toxicity        | EL50<br>mg/l   | > 1000   | 48 h      | Daphnia magna                 | REACh<br>Registration<br>Dossier      | other: REACH<br>Guidance on<br>QSARs R.6 |
| 68937-41-7 | Triaryl phosphate isoprop       | ylated         |          |           |                               |                                       |  |
|            | Acute fish toxicity             | LC50<br>mg/l   | 10,8     | 96 h      | Pimephales promelas           | REACh<br>Registration<br>Dossier      | OECD Guideline<br>203                    |
|            | Acute algae toxicity            | ErC50<br>mg/l  | > 2,5    | 72 h      | Raphidocelis<br>subcapitata   | REACh<br>Registration<br>Dossier      | EU Method C.3                            |
|            | Acute crustacea toxicity        | EC50           | 1,5 mg/l | 48 h      | Daphnia magna                 | REACh<br>Registration<br>Dossier      | OECD Guideline<br>202                    |
|            | Fish toxicity                   | NOEC<br>mg/l   | 0,0031   | 33 d      | Pimephales promelas           | REACh<br>Registration<br>Dossier      | OECD Guideline<br>210                    |
|            | Crustacea toxicity              | NOEC<br>mg/l   | 0,0415   | 21 d      | Daphnia magna                 | REACh<br>Registration<br>Dossier      | OECD Guideline<br>211                    |
|            | Acute bacteria toxicity         | EC50<br>mg/l() | > 1000   | 3 h       | activated sludge,<br>domestic | REACh<br>Registration<br>Dossier      | OECD Guideline<br>209                    |
| 68442-68-2 | Styrenated N-phenyl-benzenamine |                |          |           |                               |                                       |  |
|            | Acute fish toxicity             | LC50           | 920 mg/l | 96 h      | Danio rerio                   | REACh<br>Registration<br>Dossier      | OECD Guideline<br>203                    |
|            | Acute algae toxicity            | ErC50<br>mg/l  | 1,564    | 72 h      | Desmodesmus<br>subspicatus    | SSS QSAR<br>Prediction Team<br>(2016) | other: as<br>mentioned below             |
|            | Acute crustacea toxicity        | EC50<br>mg/l   | 0,051    | 48 h      | Daphnia magna                 | SSS QSAR<br>Prediction Team<br>(2016) | other: as<br>mentioned below             |

## 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

## 12.3. Bioaccumulative potential

No data available

## Partition coefficient n-octanol/water

| CAS No     | Chemical name                   | Log Pow           |
|------------|---------------------------------|-------------------|
| 9003-29-6  | Polybutenes                     | 7,6 - 7,8         |
| 68937-41-7 | Triaryl phosphate isopropylated | 85000 -<br>150000 |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | >= 32967          |

according to Regulation (EC) No 1907/2006

### **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 10 of 13

BCF

| CAS No     | Chemical name                   | BCF    | Species             | Source               |
|------------|---------------------------------|--------|---------------------|----------------------|
| 9003-29-6  | Polybutenes                     | 144,54 |                     | EPA (2021)           |
| 68937-41-7 | Triaryl phosphate isopropylated | 225    | Lepomis macrochirus | REACh Registration D |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | 531,1  |                     | REACh Registration D |

#### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No data available

### Further information

Do not allow uncontrolled leakage of product into the environment.

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

#### Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

#### List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

#### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be disposed of.

#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

| 14.1. UN number or ID number:            | - |
|--|---|
| 14.2. UN proper shipping name:           | - |
| 14.3. Transport hazard class(es):        | - |
| 14.4. Packing group:                     | - |
| Inland waterways transport (ADN)         |   |
| 14.1. UN number or ID number:            | - |
| 14.2. UN proper shipping name:           | - |
| 14.3. Transport hazard class(es):        | - |
| 14.4. Packing group:                     | - |
| Marine transport (IMDG)                  |   |
| 14.1. UN number or ID number:            | - |
| 14.2. UN proper shipping name:           | - |
| <u>14.3. Transport hazard class(es):</u> | - |
| 14.4. Packing group:                     | - |
| Air transport (ICAO-TI/IATA-DGR)         |   |
| 14.1. UN number or ID number:            | - |
|  |   |

according to Regulation (EC) No 1907/2006

|   | ADDINOL Chain Lube XHT 150                               |               |
|---|--|---------------|
| Revision date: 27.08.2024                                       | Product code: 766023                                     | Page 11 of 13 |
| 14.2. UN proper shipping name:                                  | -  |               |
| 14.3. Transport hazard class(es):                               | -  |               |
| 14.4. Packing group:  | -  |               |
| 14.5. Environmental hazards                                     |  |               |
| ENVIRONMENTALLY HAZARDOUS:                                      | No   |               |
| 14.6. Special precautions for user                              |  |               |
|   | easures for safe transport must be followed.             |               |
| 14.7. Maritime transport in bulk according to<br>not applicable | <u>o IMO instruments</u>                                 |               |
| Other applicable information                                    |  |               |
| No dangerous good in sense of these t                           | ransport regulations.                                    |               |
| SECTION 15: Regulatory information                              |  |               |
| 15.1. Safety, health and environmental regul                    | ations/legislation specific for the substance or mixture |               |
| EU regulatory information                                       |  |               |
| Restrictions on use (REACH, annex XVII):<br>Entry 75            |  |               |
| Information according to Directive 2012/18/EU (SEVESO III):     | Not subject to 2012/18/EU (SEVESO III)                   |               |
| National regulatory information                                 |  |               |
| Water hazard class (D):   | 3 - highly hazardous to water                            |               |
| 15.2. Chemical safety assessment                                |  |               |
|   |  |               |

## **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s): 2,3,5,7,8,9,10,12,15.

according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 12 of 13

### Abbreviations and acronyms

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: RID - Regulation concerning the International Carriage of Dangerous Goods by Rail: RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

| Classification          | Classification procedure |
|-------------------------|--------------------------|
| Aquatic Chronic 2; H411 | Calculation method       |

#### Relevant H and EUH statements (number and full text)

| H304   | May be fatal if swallowed and enters airways.                            |
|--------|--|
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H373   | May cause damage to organs through prolonged or repeated exposure.       |
| H410   | Very toxic to aquatic life with long lasting effects.                    |
| H411   | Toxic to aquatic life with long lasting effects.                         |
| H413   | May cause long lasting harmful effects to aquatic life.                  |
|        |  |

#### **Further Information**

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 150**

Revision date: 27.08.2024

Product code: 766023

Page 13 of 13

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)