



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Chain Lube XHT 150

Print date: 04.03.2014

Product code: 766023

Page 1 of 7

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

ADDINOL Chain Lube XHT 150

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Lubricant and additive.

##### 1.3. Details of the supplier of the safety data sheet

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-201	Telefax: +49 (0) 3461 845-561
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

**1.4. Emergency telephone number:** +49 (0) 3461 845-201 - This number is serviced during office hours.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

###### GHS classification

Hazard categories:  
 Hazardous to the aquatic environment: Aquatic Chronic 3  
 Hazard Statements:  
 Harmful to aquatic life with long lasting effects.

##### 2.2. Label elements

###### Hazard statements

H412 Harmful to aquatic life with long lasting effects.

###### Precautionary statements

P273 Avoid release to the environment.  
 P501

###### Additional advice on labelling

There is no requirement for the product to be specially labelled according to EC directives or the corresponding national laws.

##### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
 Process vapors can irritate airways, skin and eyes.  
 Do not allow uncontrolled leakage of product into the environment.

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures



## Safety Data Sheet



according to Regulation (EC) No 1907/2006

### ADDINOL Chain Lube XHT 150

Print date: 04.03.2014

Product code: 766023

Page 2 of 7

#### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
253-138-0	Trimellitat Ester	< 50 %
	R53	
	Aquatic Chronic 4; H413	
500-183-1	1-Decene homopolymer, hydrogenated	< 20 %
68037-01-4		
	Asp. Tox. 1; H304	
01-2119486452-34		
273-066-3	Triaryl phosphate isopropylated	< 1,75 %
68937-41-7	N - Dangerous for the environment R51-53	
	Aquatic Chronic 2; H411	
204-112-2	Triphenyl phosphate	< 1,25 %
115-86-6	N - Dangerous for the environment R50-53	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410	
233-593-1	4,4'-Methylene bis(dibutylthiocarbamate)	0,50 %
10254-57-6	R52-53	
	Aquatic Chronic 4; H413	
201-245-8	4,4'-isopropylidenediphenol	< 0,1 %
80-05-7	Xi - Irritant R36/37/38-43	
	Eye Dam. 1, Skin Sens. 1, Repr. 2, STOT SE 3; H318 H317 H361f H335	

Full text of R and H phrases: see Section 16.

#### Further Information

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

##### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

##### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Chain Lube XHT 150

Print date: 04.03.2014

Product code: 766023

Page 3 of 7

#### After ingestion

Do not induce vomiting. Rinse mouth immediately and drink large quantities of water. Immediately get medical attention.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

#### Extinguishing media which must not be used for safety reasons

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). Carbon black.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear respiratory protection when in the presence of vapour, dust, and aerosols. Avoid contact with skin, eye and clothing.

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well ventilated zones or use proper respiratory protection. Avoid oil mist In case of open handling equipment with built-in suction must be used. Avoid contact with skin, eye and clothing.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of dampness.

#### Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.  
Keep away from: Oxidizing agents.

#### Further information on storage conditions

Recommended storage temperature: 10 - 30°C



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Chain Lube XHT 150

Print date: 04.03.2014

Product code: 766023

Page 4 of 7

Protect against: heat. UV-radiation/sunlight.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
80-05-7	Bisphenol A (4,4'-isopropylidenediphenol) (inhalable dust)	-	10		TWA (8 h)	EU
		-	-		STEL (15 min)	EU
115-86-6	Triphenyl phosphate	-	3		TWA (8 h)	
		-	6		STEL (15 min)	

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

### 8.2. Exposure controls



#### Occupational exposure controls

Provide for sufficient ventilation and punctiform suction at critical points.

#### Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing.

Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn.

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Eye protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Chain Lube XHT 150

Print date: 04.03.2014

Product code: 766023

Page 5 of 7

cleaning rags into your trouser pockets.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow - brown
Odour:	characteristic

#### Test method

#### Changes in the physical state

Boiling point:	> 200 °C
Flash point:	278 °C DIN ISO 2592
Ignition temperature:	< 350 °C DIN 51794
Density (at 15 °C):	0,947 g/cm <sup>3</sup> DIN 51757
Water solubility:	virtually insoluble
Viscosity / kinematic: (at 40 °C)	145 mm <sup>2</sup> /s DIN 51562

## SECTION 10: Stability and reactivity

### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.  
Do not overheat to avoid decomposition by heat.

### 10.5. Incompatible materials

Reacts with : Oxidizing agents, strong.

### 10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). Carbon black.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Preparation related information:

Acute toxicity, oral, Rat. LD50: > 2000 mg/kg

Test was carried out with a similar formulation.

#### Specific effects in experiment on an animal

No data available

#### Irritation and corrosivity

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Sensitising effects

Contains: < 0,10% 4,4'-Isopropylidendiphenol. May produce an allergic reaction.

#### Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Carcinogenic/mutagenic/toxic effects for reproduction

No data available



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Chain Lube XHT 150

Print date: 04.03.2014

Product code: 766023

Page 6 of 7

#### SECTION 12: Ecological information

##### 12.1. Toxicity

No data available

Preparation not tested.

##### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

##### 12.3. Bioaccumulative potential

No data available

##### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

##### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

##### 12.6. Other adverse effects

No data available

##### **Further information**

Do not allow uncontrolled leakage of product into the environment.

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

###### **Advice on disposal**

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

###### **Waste disposal number of waste from residues/unused products**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils  
Classified as hazardous waste.

###### **Contaminated packaging**

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning. Packing which cannot be properly cleaned must be thrown away. Waste disposal according to official state regulations.

#### SECTION 14: Transport information

##### **Land transport (ADR/RID)**

14.1. UN number: -

##### **Inland waterways transport (ADN)**

14.1. UN number: -

##### **Marine transport (IMDG)**

14.1. UN number: -

##### **Air transport (ICAO)**

14.1. UN number: -

##### 14.5. Environmental hazards

Dangerous for the environment: no



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Chain Lube XHT 150

Print date: 04.03.2014

Product code: 766023

Page 7 of 7

#### Other applicable information

Not a hazardous material with respect to these transportation regulations.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulatory information

Water contaminating class (D): 2 - water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Full text of R phrases referred to under Sections 2 and 3

36/37/38	Irritating to eyes, respiratory system and skin.
43	May cause sensitisation by skin contact.
50	Very toxic to aquatic organisms.
51	Toxic to aquatic organisms.
52	Harmful to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.

#### Full text of H statements referred to under Sections 2 and 3

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

#### Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*