according to Regulation (EC) No 1907/2006

ADDINOL	Guideway	Oil XG	68
---------	----------	--------	----

Revision date: 09.02.2022

Product code: 763001

Page 1 of 13

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

ADDINOL Guideway Oil XG 68

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant and additive.

### 1.3. Details of the supplier of the safety data sheet

# Manufacturer

Manufacturer		
Company name:	ADDINOL Lube Oil GmbH Gebäude 4609	
Street:		
	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0	Telefax:+49 (0) 3461 845-555
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	
Supplier		
Company name:	GEM OILS LIMITED	
Place:	IRL-H12 E4W2 Regaskin Co. Cavan	
Telephone:	+353 49 4378116	Telefax: +353 49 4368329
e-mail:	sales@gemoils.ie	
Contact person:	GEM OILS LIMITED	Telephone: +353 49 4378116
e-mail:	sales@gemoils.ie	
Internet:	https://gemoils.ie/	
1.4. Emergency telephone	Healthcare Professionals: +353 (1) 809	2566 (24 hour service)
number.		

number:

SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## 2.2. Label elements

H412

#### Regulation (EC) No 1272/2008

# Hazard statements

Harmful to aquatic life with long lasting effects.

# **Precautionary statements**

P273 P501 Avoid release to the environment.

Dispose of contents/container to industrial incineration plant.

#### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 2 of 13

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

## Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	·			
64742-54-7	2-54-7 Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	265-157-1		01-2119484627-25		
	Asp. Tox. 1; H304	•			
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(e	urated)-alkylamines	0.1 - < 0.3 %		
	627-034-4		01-2119473797-19		
	Acute Tox. 4, Skin Corr. 1B, Eye Da Aquatic Chronic 1; H302 H314 H31	. Tox. 1, Aquatic Acute 1,			
104-76-7	2-Ethylhexan-1-ol		< 0.1 %		
	203-234-3				
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit.	2, STOT SE 3; H332 H315 H319 H33	35		

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity					
	Specific Conc. I	ecific Conc. Limits, M-factors and ATE						
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	60 - < 80 %					
	dermal: LD50 =	= > 5000 mg/kg; oral: LD50 = > 5000 mg/kg						
1213789-63-9	627-034-4	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated) -alkylamines	0.1 - < 0.3 %					
	dermal: LD50 = M chron.; H410	= > 2000 mg/kg; oral: LD50 = 1689 mg/kg						
104-76-7	203-234-3	2-Ethylhexan-1-ol	< 0.1 %					
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = ca. 2047 mg/kg							

### Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

## After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids

according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 3 of 13

apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water. Sand.

Unsuitable extinguishing media

### High power water jet.

## 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. Phosphorus oxides. carbon black.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.3. Methods and material for containment and cleaning up

### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

# 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory) Disposal: see section 13

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered,

according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 4 of 13

arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Oxidizing agents.

### Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

# 7.3. Specific end use(s)

Further information: see technical data sheet.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

## Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
104-76-7	2-Ethylhexan-1-ol	1	5.4		TWA (8 h)	

according to Regulation (EC) No 1907/2006

# ADDINOL Guideway Oil XG 68

Revision date: 09.02.2022

Product code: 763001

Page 5 of 13

# **DNEL/DMEL** values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy	y paraffinic; Baseoil - unspecified	•	•
Worker DNEL	_, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL	_, long-term	inhalation	local	5,58 mg/m³
Worker DNEL	., long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	local	1,19 mg/m³
Consumer DN	NEL, long-term	oral	systemic	0,74 mg/kg bw/day
1213789-63- 9	(Z)-octadec-9-enylamine, C16-18-(even n	umbered, saturated and unsaturated)	-alkylamines	
Worker DNEL	, long-term	inhalation	systemic	0,38 mg/m³
Worker DNEL	_, long-term	inhalation	local	1 mg/m³
Worker DNEL	_, acute	inhalation	local	1 mg/m³
Consumer DN	NEL, long-term	inhalation	systemic	0,035 mg/m³
Consumer DN	NEL, long-term	oral	systemic	0,04 mg/kg bw/day
104-76-7	2-Ethylhexan-1-ol			
Worker DNEL	, long-term	inhalation	systemic	12,8 mg/m <sup>3</sup>
Worker DNEL	_, long-term	inhalation	local	53,2 mg/m <sup>3</sup>
Worker DNEL	_, acute	inhalation	local	53,2 mg/m <sup>3</sup>
Worker DNEL	_, long-term	dermal	systemic	23 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	systemic	2,3 mg/m <sup>3</sup>
Consumer DN	NEL, long-term	inhalation	local	26,6 mg/m <sup>3</sup>
Consumer DN	NEL, acute	inhalation	local	26,6 mg/m <sup>3</sup>
Consumer DN	NEL, long-term	dermal	systemic	11,4 mg/kg bw/day
Consumer DN	NEL, long-term	oral	systemic	1,1 mg/kg bw/day

according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 6 of 13

#### **PNEC** values

CAS No	Substance	
Environmenta	l compartment	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary po	isoning	9,33 mg/kg
1213789-63- 9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkyla	mines
Freshwater		0,00026 mg/l
Freshwater (ir	termittent releases)	0,0016 mg/l
Marine water		0,000026 mg/l
Freshwater se	diment	3,76 mg/kg
Marine sedime	ent	0,376 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	0,55 mg/l
Soil		10 mg/kg
104-76-7	2-Ethylhexan-1-ol	
Freshwater		0,017 mg/l
Freshwater (ir	termittent releases)	0,17 mg/l
Marine water		0,002 mg/l
Freshwater se	diment	0,284 mg/kg
Marine sedime	0,028 mg/kg	
Secondary po	isoning	55 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	10 mg/l
Soil		0,047 mg/kg

#### Additional advice on limit values

Recommended limit value for oil mist TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

## 8.2. Exposure controls





### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

# Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 7 of 13

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

# Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

## **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Colour:	liquid brown		
Odour:	like: mineral oil.		
			Test method
Changes in the physical state			
Melting point/freezing point:		No data available	
Boiling point or initial boiling point and		not determined	
boiling range:			
Pour point:			ASTM D 7346
Flash point:		257 °C	DIN EN ISO 2592
Flammability			
Solid/liquid:		No data available	
Gas:		No data available	
Explosive properties No data available			
Lower explosion limits:		No data available	
Upper explosion limits:		No data available	
Auto-ignition temperature:		not determined	
Self-ignition temperature			
Solid:		No data available	
Gas:		No data available	
Decomposition temperature:		No data available	
pH-Value:		No data available	
Viscosity / kinematic: (at 40 °C)		68,4 mm²/s	ASTM D 7042
Water solubility:		virtually insoluble	
Solubility in other solvents No data available			
Partition coefficient n-octanol/water:		No data available	
Vapour pressure:		No data available	
Density (at 15 °C):		0,874 g/cm³	DIN 51757
Relative vapour density:		No data available	
.2. Other information			

#### 9.2. Other information

according to Regulation (EC) No 1907/2006

ADDINOL	Guideway	Oil XG 68
---------	----------	-----------

Revision date: 09.02.2022

Product code: 763001

No data available

Page 8 of 13

Oxidizing properties No data available

Evaporation rate: Further Information

No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

# 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

# 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

# 10.5. Incompatible materials

No data available

# 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. Phosphorus oxides. carbon black.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

# according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 9 of 13

CAS No	Chemical name	Chemical name						
	Exposure route	Dose		Species	Source	Method		
64742-54-7	Distillates (petroleum), hy	drotreated h	eavy paraffir	nic; Baseoil - unspecified				
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402		
1213789-63- 9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines							
	oral	LD50 mg/kg	1689	Rat	Study report (1993)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1985)	OECD Guideline 402		
104-76-7	2-Ethylhexan-1-ol							
	oral	LD50 mg/kg	ca. 2047	Rat	Publication (1969)	OECD Guideline 401		
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

### Aspiration hazard

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards

## Endocrine disrupting properties

not applicable

# **SECTION 12: Ecological information**

# 12.1. Toxicity

No data available

Mixture not tested.

# according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 10 of 13

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hy	drotreated h	neavy paraffir	nic; Base	oil - unspecified		
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h			
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
1213789-63- 9	(Z)-octadec-9-enylamine,	C16-18-(ev	en numbered	d, saturat	ed and unsaturated)-alky	lamines	
	Acute fish toxicity	LC50 mg/l	0,84	96 h	Danio rerio	Study report (2006)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,39	72 h	Desmodesmus subspicatus	Study report (2002)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,32	48 h	Daphnia magna	Study report (2006)	OECD Guideline 202
	Crustacea toxicity	NOEC mg/l	0,013	21 d	Daphnia magna	Study report (2002)	OECD Guideline 211
	Acute bacteria toxicity	(EC50	32 mg/l)	3 h	activated sludge of a predominantly domestic sewag	Study report (1989)	OECD Guideline 209
104-76-7	2-Ethylhexan-1-ol						
	Acute fish toxicity	LC50 mg/l	17,1	96 h	Leuciscus idus melanotus	Study report (1991)	EU Method C.1
	Acute algae toxicity	ErC50 mg/l	11,5	72 h	Desmodesmus subspicatus	Study report (1991)	EU Method C.3
	Acute crustacea toxicity	EC50	39 mg/l	48 h	Daphnia magna	Study report (1991)	EU Method C.2

# 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

# 12.3. Bioaccumulative potential

No data available

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	5,16
104-76-7	2-Ethylhexan-1-ol	2,9

BCF

CAS No	Chemical name	BCF	Species	Source
	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated) -alkylamines	173		Environmental Toxico

# 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# 12.6. Endocrine disrupting properties

according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 11 of 13

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

No data available

# **Further information**

Do not allow uncontrolled leakage of product into the environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

#### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

## Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number or ID number:	-				
14.2. UN proper shipping name:	-				
14.3. Transport hazard class(es):	-				
14.4. Packing group:	-				
Inland waterways transport (ADN)					
14.1. UN number or ID number:	-				
14.2. UN proper shipping name:	-				
14.3. Transport hazard class(es):	-				
14.4. Packing group:	-				
Marine transport (IMDG)					
14.1. UN number or ID number:	-				
14.2. UN proper shipping name:	-				
14.3. Transport hazard class(es):	-				
14.4. Packing group:	-				
Air transport (ICAO-TI/IATA-DGR)					
14.1. UN number or ID number:	-				
14.2. UN proper shipping name:	-				
14.3. Transport hazard class(es):	-				
14.4. Packing group:	-				
14.5. Environmental hazards					
ENVIRONMENTALLY HAZARDOUS:	No				
14.6. Special precautions for user					
Unless specified otherwise, general m	easures for safe transport must be followed.				
14.7. Maritime transport in bulk according to IMO instruments					
not applicable					

### Other applicable information

No dangerous good in sense of these transport regulations.

according to Regulation (EC) No 1907/2006

# **ADDINOL Guideway Oil XG 68**

Revision date: 09.02.2022

Product code: 763001

Page 12 of 13

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 75

#### National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,4,6,7,11,12,16.

# Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant: DIN - Standard of the German Institute for Standardisation: DNEL - Derived No-Effect Level: DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: RID - Regulation concerning the International Carriage of Dangerous Goods by Rail: RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

# Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method
Relevant H and EUH s	tatements (number and full text)
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

according to Regulation (EC) No 1907/2006

ADDINOL Guideway Oil XG 68					
Revision date: 09.02.2022	Product code: 763001	Page 13 of 13			
H332	Harmful if inhaled.				
H335	May cause respiratory irritation.				
H373	May cause damage to organs through prolonged or repeated exposure.				
H400	Very toxic to aquatic life.				
H410	Very toxic to aquatic life with long lasting effects.				
H412	Harmful to aquatic life with long lasting effects.				

### **Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)