according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Gear Oil CLP 220

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Gearbox oil.

For industrial purposes only.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

E-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

internet. www.addinoi.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: GEM OILS LIMITED

Place: IRL-H12K298 Regaskin Co. Cavan

Telephone: +353 49 4378116 Telefax: +353 49 4368329

E-mail: sales@gemoils.ie

Contact person: GEM OILS LIMITED Telephone: +353 49 4378116

E-mail: sales@gemoils.ie Internet: https://gemoils.ie/

1.4. Emergency telephone Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Regulation (EC) No 1272/2008

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 2 of 12

Relevant ingredients

| CAS No | Chemical name | | | | |
|------------|---|--------------------|------------------|-------------|--|
| | EC No | Index No | REACH No | | |
| | Classification (Regulation (EC) No | 1272/2008) | | | |
| 64742-54-7 | Distillates (petroleum), hydrotreated | l heavy paraffinic | | 40 - < 60 % | |
| | 265-157-1 | | 01-2119484627-25 | | |
| | Asp. Tox. 1; H304 | | | | |
| 68937-96-2 | Di-tert-butyl-Polysulfides | | | 0.5 - < 1 % | |
| | 273-103-3 | | 01-2119540515-43 | | |
| | Skin Sens. 1B, Aquatic Chronic 3; H317 H412 | | | | |
| 68955-53-3 | Amines, C10-C14-tert-alkyl | | | < 0.1 % | |
| | 701-175-2 | | 01-2119456798-18 | | |
| | Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H318 H317 H400 H410 | | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|------------|------------------|--|-------------|
| | Specific Conc. I | Limits, M-factors and ATE | |
| 64742-54-7 | 265-157-1 | Distillates (petroleum), hydrotreated heavy paraffinic | |
| | dermal: LD50 = | = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg | |
| 68937-96-2 | 273-103-3 | Di-tert-butyl-Polysulfides | 0.5 - < 1 % |
| | Skin Sens. 1B; | H317: >= 46 - 100 | |
| 68955-53-3 | 701-175-2 | Amines, C10-C14-tert-alkyl | < 0.1 % |
| | LD50 = 251 mg | inhalation: LC50 = >= 157 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = > 500 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1 | |

Further Information

This mixture does not contain any substances which either present a health or environmental hazard according to Regulation (EC) No. 1272/2008 or have an occupational exposure limit assigned.

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Protect skin by using skin protective cream. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 3 of 12

Rinse mouth immediately and drink plenty of water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides, carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 4 of 12

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat. Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|--|----------------|----------|-----------------------|
| DNEL type | | Exposure route | Effect | Value |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic | | | |
| Worker DNEL | , long-term | inhalation | systemic | 2,73 mg/m³ |
| Worker DNEL | , long-term | inhalation | local | 5,58 mg/m³ |
| Worker DNEL | long-term | dermal | systemic | 0,97 mg/kg bw/day |
| Consumer DN | EL, long-term | inhalation | local | 1,19 mg/m³ |
| Consumer DN | EL, long-term | oral | systemic | 0,74 mg/kg bw/day |
| 68937-96-2 | Di-tert-butyl-Polysulfides | | | |
| Worker DNEL | , long-term | inhalation | systemic | 3,29 mg/m³ |
| Worker DNEL | long-term | dermal | systemic | 4,67 mg/kg bw/day |
| Consumer DN | EL, long-term | inhalation | systemic | 0,58 mg/m³ |
| Consumer DNEL, long-term | | dermal | systemic | 1,67 mg/kg bw/day |
| Consumer DN | EL, long-term | oral | systemic | 0,167 mg/kg bw/day |
| 68955-53-3 | Amines, C10-C14-tert-alkyl | | | |
| Worker DNEL | , long-term | inhalation | systemic | 12,5 mg/m³ |
| Worker DNEL, long-term | | inhalation | local | 12,1 mg/m³ |
| Consumer DNEL, long-term | | inhalation | systemic | 2,5 mg/m³ |
| Consumer DNEL, long-term | | inhalation | local | 1,2 mg/m³ |
| Consumer DN | EL, long-term | oral | systemic | 0,35 mg/kg bw/day |

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 5 of 12

PNEC values

| Value |
|---------------|
| |
| 9,33 mg/kg |
| |
| 0,00024 mg/l |
| 0,002 mg/l |
| 0,000024 mg/l |
| 0,94 mg/kg |
| 0,094 mg/kg |
| 6,66 mg/kg |
| 4,51 mg/l |
| 0,0181 mg/kg |
| |
| 0,001 mg/l |
| 0,004 mg/l |
| 0 mg/l |
| 2,14 mg/kg |
| 0,214 mg/kg |
| 4,71 mg/kg |
| 0,635 mg/l |
| 0,428 mg/kg |
| |

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

Does not contain substances above concentration limits fixing an occupational exposure limit.

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 6 of 12

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: brown

Odour: like: mineral oil. Odour threshold: not determined

Test method

No data available Melting point/freezing point: Boiling point or initial boiling point and not determined

boiling range:

(at 40 °C)

No data available Flammability: Lower explosion limits: No data available Upper explosion limits: No data available

Flash point: 270 °C DIN EN ISO 2592

Auto-ignition temperature: not determined No data available Decomposition temperature: pH-Value: not applicable

Viscosity / kinematic: 220 mm²/s ASTM D 7042

Water solubility: Solubility in other solvents

virtually insoluble

No data available

Partition coefficient n-octanol/water: No data available Vapour pressure: No data available

Vapour pressure: **DIN 51640**

0,890 g/cm3 DIN 51757 Density (at 15 °C):

Relative vapour density: No data available Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties No data available Self-ignition temperature

> Solid: No data available Gas: No data available

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 7 of 12

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Pour point: -27 °C ASTM D 7346

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. carbon black. No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No | Chemical name | | | | | |
|------------|--|---------------|-----------|---------|---------------------|--------------------|
| | Exposure route | Dose | | Species | Source | Method |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic | | | | | |
| | oral | LD50 mg/kg | > 5000 | Rat | Study report (1982) | OECD Guideline 401 |
| | dermal | LD50 mg/kg | > 5000 | Rabbit | Study report (1982) | OECD Guideline 402 |
| 68955-53-3 | Amines, C10-C14-tert-alkyl | | | | | |
| | oral | LD50 mg/kg | > 500 | Rat | Study report (1993) | OECD Guideline 401 |
| | dermal | LD50 mg/kg | 251 | Rat | Study report (1993) | OECD Guideline 402 |
| | inhalation (4 h) vapour | LC50 mg/l | >= 157 | Rat | Study report (2001) | OECD Guideline 403 |
| | inhalation dust/mist | ATE | 0,05 mg/l | | | |

Irritation and corrosivity

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 8 of 12

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

| CAS No | Chemical name | | | | | | | |
|------------|-----------------------------|--|----------|-----------|--|---|---|--|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method | |
| 64742-54-7 | Distillates (petroleum), hy | Distillates (petroleum), hydrotreated heavy paraffinic | | | | | | |
| | Acute fish toxicity | LL50 mg/l | > 100 | 96 h | Pimephales promelas | Study report (1995) | OECD Guideline 203 | |
| | Acute algae toxicity | ErC50 mg/l | >100 | 72 h | | | | |
| | Fish toxicity | NOEC mg/l | >= 1000 | 14 d | Oncorhynchus mykiss | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a | |
| 68937-96-2 | Di-tert-butyl-Polysulfides | | | | | | | |
| | Acute algae toxicity | ErC50 mg/l | > 100 | 72 h | Raphidocelis subcapitata | Study report (2012) | OECD Guideline 201 | |
| | Acute crustacea toxicity | EL50 | 63 mg/l | 48 h | Daphnia magna | Study report (2013) | OECD Guideline 202 | |
| 68955-53-3 | Amines, C10-C14-tert-alkyl | | | | | | | |
| | Acute fish toxicity | LC50 | 1,3 mg/l | 96 h | Oncorhynchus mykiss | Study report (1994) | OECD Guideline 203 | |
| | Acute algae toxicity | ErC50 mg/l | 0,44 | 72 h | Raphidocelis subcapitata | Study report (1994) | OECD Guideline 201 | |
| | Acute crustacea toxicity | EC50 | 4,1 mg/l | 48 h | Daphnia magna | Study report (1984) | OECD Guideline 202 | |
| | Fish toxicity | NOEC mg/l | 0,078 | 96 d | Oncorhynchus mykiss | Study report (2002) | OECD Guideline 210 | |
| | Acute bacteria toxicity | EC50 mg/l () | 63,5 | 0,5 h | activated sludge of a predominantly domestic sewag | Study report (2008) | OECD Guideline 209 | |

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 9 of 12

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|----------------------------|---------|
| 68937-96-2 | Di-tert-butyl-Polysulfides | 5,6 |
| 68955-53-3 | Amines, C10-C14-tert-alkyl | 2,9 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|------------|----------------------------|-------|---------------------|---------------------|
| 68937-96-2 | Di-tert-butyl-Polysulfides | 0,006 | Lepomis macrochirus | Study report (2015) |

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

according to Regulation (EC) No 1907/2006

| | ADDINOL Gear Oil CLP 220 | |
|---------------------------|--------------------------|---------------|
| Revision date: 05.08.2024 | Product code: 741010 | Page 10 of 12 |

Marine transport (IMDG)

14.1. UN number or ID number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,6,8,9.

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 11 of 12

Abbreviations and acronyms

Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Corr: Skin corrosion
Eye Dam: Eye damage
Skin Sens: Skin sensitisation
Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard
For abbreviations and acronyms, see: ECHA Guidance on information

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ASTM - American Society for the Testing of Materials: ATE - Acute Toxicity Estimates; bw - Body weight: CAO -Cargo Aircraft Only: CAS - Chemical Abstracts Service: CMR - Carcinogen, Mutagen or Reproductive Toxicant: DIN - Standard of the German Institute for Standardisation: DNEL - Derived No-Effect Level: DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: RID - Regulation concerning the International Carriage of Dangerous Goods by Rail: RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Relevant H and EUH statements (number and full text)

| H302 | Harmful if swallowed. |
|--------|---|
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH210 | Safety data sheet available on request. |

Further Information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

according to Regulation (EC) No 1907/2006

ADDINOL Gear Oil CLP 220

Revision date: 05.08.2024 Product code: 741010 Page 12 of 12

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)