

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDIFLON PTFE Fluid Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Aerosol - Lubricant, Parting agent.

1.3. Details of the supplier of the safety data sheet

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0	Telefax: +49 (0) 3461 845-555
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

1.4. Emergency telephone number: +49 (0) 3461 845 222 - Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P102	Keep out of reach of children.
------	--------------------------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 2 of 11

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

80 % by mass of the contents are flammable.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



Hazard statements

H229

Precautionary statements

P210-P251-P410+P412

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	30 - 35 %
	200-661-7	
	603-117-00-0	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
115-10-6	dimethyl ether	15 - 20 %
	204-065-8	
	603-019-00-8	
	Flam. Gas 1; H220	

Full text of H and EUH statements: see section 16.

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 3 of 11

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

Flammable.. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 4 of 11

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eye and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
106-97-8	Aliphatic hydrocarbon gases, Alkanes (C1-C4), Butane	1000	-		TWA (8 h)	
74-98-6	Aliphatic hydrocarbon gases, Alkanes (C1-C4), Propane	1000	-		TWA (8 h)	
115-10-6	Dimethyl ether	1000	1920		TWA (8 h)	
67-63-0	Isopropyl alcohol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 5 of 11

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

Additional advice on limit values

source:

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: gaseous
 Colour: white
 Odour: characteristic

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: not applicable

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 6 of 11

Initial boiling point and boiling range: < -20 °C
Flash point: < -20 °C DIN EN ISO 2592

Flammability

Solid: not applicable
Gas: not applicable

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Lower explosion limits: 2 vol. %
Upper explosion limits: 26,2 vol. %
Ignition temperature: 235 °C DIN 51794

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

No data available

Vapour pressure: not determined
(at 20 °C)

Density (at 20 °C): 0,748 g/cm³ DIN 51757

Water solubility: insoluble
(at 20 °C)

Solubility in other solvents

No data available

Partition coefficient: not determined

Viscosity / kinematic: not applicable

Vapour density: not determined

Evaporation rate: No data available

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

10.5. Incompatible materials

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 7 of 11

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

Vapours may form explosive mixtures with air.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg	5280	Rat	
	dermal	LD50 mg/kg	12800	Rabbit	
	inhalation (4 h) vapour	LC50	47,5 mg/l	Rat	

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information

12.1. Toxicity

No data available

Mixture not tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Pseudokirchneriella subcapitata	
	Crustacea toxicity	NOEC mg/l	13299	2 d	Daphnia magna	

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1

12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1



Classification code:	5F
Special Provisions:	190 327 344 625

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 9 of 11

Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 10 of 11

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: butane

2010/75/EU (VOC): 75,236 % (562,762 g/L)

2004/42/EC (VOC): 75,236 % (562,762 g/L)

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC , 2008/47/EC, Aerosolrichtlinie (75/324/EWG)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDIFLON PTFE Fluid Spray

Revision date: 19.06.2019

Product code: 717230

Page 11 of 11

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)