# **Safety Data Sheet**

according to UK REACH Regulation

### **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

ADDINOL Lube Oil CL 10

UFI: 1Y76-T42V-J206-H4UQ

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Lubricant and additive.

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Specialised Products (Western) Limited
Street: 76 Cobham Road, Ferndown Industrial Estate

Place: GB-BH21 7RN Wimborne, Dorset

Telephone: +44 1202 891393 Telefax: +44 1202 876908

e-mail: sales@specialisedproducts.co.uk
Internet: http://specialisedproducts.co.uk

1.4. Emergency telephone +44 1202 891393 - This number is serviced during office hours.

number:

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## 2.2. Label elements

### **GB CLP Regulation**

### Hazard components for labelling

Distillates (petroleum), hydrotreated light paraffinic Baseoil - unspecified Distillates (petroleum), heavy hydrocracked; Base oil unspecified

Signal word: Danger

Pictograms:



### **Hazard statements**

H304 May be fatal if swallowed and enters airways.

## according to UK REACH Regulation

### **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 2 of 12

### **Precautionary statements**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to industrial incineration plant.

### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

## 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### **Chemical characterization**

Mixture of mineral oil rafffinates and additives.

### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-55-8	Distillates (petroleum), hydrotreated	d light paraffinic Baseoil - unspecified	I	> 70 %
	265-158-7		01-2119487077-29	
	Asp. Tox. 1; H304			
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified			
	265-077-7		01-2119486951-26	
	Asp. Tox. 1; H304			
128-39-2	2,6-di-tert-butylphenol			< 0,20 %
	204-884-0		01-2119490822-33	
	Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H315 H400 H410			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

	positio cono: Elittico, in factoro ana 711				
CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic Baseoil - unspecified	> 70 %		
	dermal: LD50 =	= > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			
64741-76-0	265-077-7	Distillates (petroleum), heavy hydrocracked; Base oil unspecified	< 25 %		
	inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg				
128-39-2	204-884-0	2,6-di-tert-butylphenol	< 0,20 %		
	oral: LD50 = > Aquatic Chronic	5000 mg/kg Aquatic Acute 1; H400: M=1 c 1; H410: M=1			

## **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

# **SECTION 4: First aid measures**

# **Safety Data Sheet**

according to UK REACH Regulation

#### **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 3 of 12

### 4.1. Description of first aid measures

#### General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Give activated carbon, in order to reduce the resorption in the gastro-enteric tract. Call a physician immediately.

Caution if victim vomits: Risk of aspiration!

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

## 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor

# **Safety Data Sheet**

according to UK REACH Regulation

### **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 4 of 12

according to the environmental legislation.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep/Store only in original container.

## Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

## Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat. Recommended storage temperature: 5 - 40°C

### 7.3. Specific end use(s)

Further information: see technical data sheet.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

according to UK REACH Regulation

# **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 5 of 12

## **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-55-8	Distillates (petroleum), hydrotreated light paraf	finic Baseoil - unspecified	•	
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³
Worker DNEL,	long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	1,19 mg/m³
Consumer DN	EL, long-term	oral	systemic	0,74 mg/kg bw/day
64741-76-0	Distillates (petroleum), heavy hydrocracked; B	ase oil unspecified		
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL, long-term		inhalation	local	5,58 mg/m³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	1,19 mg/m³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
128-39-2	2,6-di-tert-butylphenol			
Consumer DN	EL, long-term	dermal	systemic	6,75 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	6,75 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	20,9 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	70,61 mg/m³
Worker DNEL, long-term		dermal	systemic	11,25 mg/kg bw/day

## **PNEC** values

CAS No	Substance		
Environmental	Environmental compartment Value		
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic Baseoil - unspecified		
Secondary pois	soning	9,33 mg/kg	
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified		
Secondary pois	coning	9,33 mg/kg	
128-39-2	2,6-di-tert-butylphenol		
Freshwater	Freshwater 0,001 mg/l		
Freshwater (intermittent releases) 0,004 mg/l		0,004 mg/l	
Marine water 0 mg/l		0 mg/l	
Freshwater sediment 0,317 mg/kg		0,317 mg/kg	
Marine sediment 0,032 mg/k		0,032 mg/kg	
Secondary poisoning 60 mg/kg		60 mg/kg	
Micro-organisms in sewage treatment plants (STP)  10 mg/l		10 mg/l	
Soil 0,697 mg/kg		0,697 mg/kg	

## Additional advice on limit values

Recommended limit value for oil mist

according to UK REACH Regulation

### **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 6 of 12

TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### 8.2. Exposure controls





### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

## **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: yellow
Odour: like: mineral oil.

Odour: IIKe: mineral oil. Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability: No data available Lower explosion limits: No data available Upper explosion limits: No data available

Flash point: 160 °C DIN EN ISO 2592

Auto-ignition temperature:

Decomposition temperature:

No data available

No data available

according to UK REACH Regulation

### **ADDINOL Lube Oil CL 10**

Product code: 741021 Revision date: 24.01.2023 Page 7 of 12

pH-Value: not applicable

Viscosity / kinematic: 10 mm<sup>2</sup>/s DIN 51562

(at 40 °C)

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: No data available Vapour pressure: No data available

Density (at 15 °C): 0.850 g/cm3 DIN 51757

Relative vapour density: No data available

### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties No data available Self-ignition temperature

> Solid: No data available No data available Gas:

Oxidizing properties No data available

Other safety characteristics

Evaporation rate: No data available

- 36 °C ASTM D 7346 Pour point:

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

## 10.5. Incompatible materials

Reacts with: Oxidizing agents, strong.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

## Acute toxicity

Based on available data, the classification criteria are not met.

No data available

Mixture not tested.

# **Safety Data Sheet**

according to UK REACH Regulation

## **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 8 of 12

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic Baseoil - unspecified					
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified					
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 mg/l	> 5000	Rabbit		
128-39-2	2,6-di-tert-butylphenol					
	oral	LD50 mg/kg	> 5000	Rat	Study report (1991)	OECD Guideline 401

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

## **Aspiration hazard**

May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

# **Endocrine disrupting properties**

not applicable

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.

No data available

Mixture not tested.

according to UK REACH Regulation

## **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 9 of 12

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64742-55-8	Distillates (petroleum), hy	drotreated li	ght paraffinio	Baseoil	- unspecified			
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203	
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
64741-76-0	Distillates (petroleum), he	avy hydrocr	acked; Base	oil unspe	ecified			
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> = 100	72 h	Alge			
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
128-39-2	2,6-di-tert-butylphenol							
	Acute fish toxicity	LC50	1,4 mg/l	96 h	Pimephales promelas	REACh Registration Dossier	OECD Guideline 204	
	Acute crustacea toxicity	EC50 mg/l	0,45	48 h	Daphnia magna	REACh Registration Dossier	other: US EPA TSCA as cited Fed. Registe	
	Crustacea toxicity	NOEC mg/l	0,035	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211	
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	a mixed population of activated sewage sludge micr	REACh Registration Dossier	OECD Guideline 209	

# 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

## 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
128-39-2	2,6-di-tert-butylphenol	4,5

## **BCF**

CAS No	Chemical name	BCF	Species	Source
128-39-2	2,6-di-tert-butylphenol	135 - 360	Cyprinus carpio	Publication (1992)

### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No data available

# **Safety Data Sheet**

according to UK REACH Regulation

#### **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 10 of 12

#### **Further information**

Do not allow uncontrolled leakage of product into the environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

#### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-

14.3. Transport hazard class(es):
14.4. Packing group:

### Inland waterways transport (ADN)

14.1. UN number or ID number:
14.2. UN proper shipping name:
14.3. Transport hazard class(es):

14.4. Packing group:

## Marine transport (IMDG)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

# Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:-14.2. UN proper shipping name:-14.3. Transport hazard class(es):-

14.4. Packing group:
14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### Other applicable information

No dangerous good in sense of these transport regulations.

### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU regulatory information**

according to UK REACH Regulation

#### **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 11 of 12

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

### **National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,6,7,9,10,11,12,15,16.

#### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only: CAS - Chemical Abstracts Service: CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

#### Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

### **Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of

according to UK REACH Regulation

## **ADDINOL Lube Oil CL 10**

Revision date: 24.01.2023 Product code: 741021 Page 12 of 12

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)