

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

ADDINOL Super Truck MD 1049

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Motor oil.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0	Telefax: +49 (0) 3461 845-555
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

Supplier

Company name:	GEM OILS LIMITED	
Place:	IRL-H12 E4W2 Regaskin Co. Cavan	
Telephone:	+353 49 4378116	Telefax: +353 49 4368329
e-mail:	sales@gemoils.ie	
Contact person:	GEM OILS LIMITED	Telephone: +353 49 4378116
e-mail:	sales@gemoils.ie	
Internet:	https://gemoils.ie/	

1.4. Emergency telephone number:

Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273	Avoid release to the environment.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH208 Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 2 of 13

2.3. Other hazards

- Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
- Spilled product must not leak into the ground.
- Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	60 - < 80 %
	265-157-1	
	01-2119484627-25	
	Asp. Tox. 1; H304	
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	5 - < 10 %
	265-090-8	
	01-2119488706-23	
	Asp. Tox. 1; H304	
36878-20-3	Bis(nonylphenyl)amine	2.5 - < 5 %
	253-249-4	
	01-2119488911-28	
	Aquatic Chronic 4; H413	
722503-68-6	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	0.3 - < 0.5 %
	682-816-2	
	01-2119985162-35	
	Skin Sens. 1, Aquatic Chronic 4; H317 H413	
121158-58-5	phenol, dodecyl-, branched	< 0.1 %
	310-154-3	
	604-092-00-9	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	60 - < 80 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64741-88-4	265-090-8	Distillates (petroleum), solvent-refined heavy paraffinic	5 - < 10 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
36878-20-3	253-249-4	Bis(nonylphenyl)amine	2.5 - < 5 %
		oral: LD50 = > 5000 mg/kg	
121158-58-5	310-154-3	phenol, dodecyl-, branched	< 0.1 %
		dermal: LD50 = ca. 15000 mg/kg; oral: LD50 = 2100 mg/kg M acute; H400: M=10 M chron.; H410: M=10	

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 3 of 13

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 4 of 13

according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
122-39-4	Diphenylamine	-	10		TWA (8 h)	
		-	20		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 5 of 13

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
36878-20-3	Bis(nonylphenyl)amine		
Worker DNEL, long-term	dermal	systemic	5 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
121158-58-5	phenol, dodecyl-, branched		
Consumer DNEL, acute	oral	systemic	1,26 mg/kg bw/day
Worker DNEL, acute	inhalation	systemic	44,18 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	166 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,79 mg/m ³
Consumer DNEL, acute	inhalation	systemic	13,26 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,075 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	
Secondary poisoning		9,33 mg/kg
36878-20-3	Bis(nonylphenyl)amine	
Freshwater		0,412 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,041 mg/l
Freshwater sediment		1 mg/kg
Marine sediment		0,1 mg/kg
121158-58-5	phenol, dodecyl-, branched	
Freshwater		0,000074 mg/l
Freshwater (intermittent releases)		0,00037 mg/l
Marine water		0,000007 mg/l
Freshwater sediment		0,226 mg/kg
Marine sediment		0,027 mg/kg
Secondary poisoning		4 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,118 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 7 of 13

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe > 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow - brown
Odour:	like: mineral oil.
Odour threshold:	not determined

Test method**Changes in the physical state**

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	not determined
Pour point:	-40 °C ASTM D 7346
Flash point:	235 °C DIN EN ISO 2592

Flammability

Solid/liquid:	No data available
Gas:	No data available

Explosive properties

No data available

Lower explosion limits:	No data available
Upper explosion limits:	No data available
Auto-ignition temperature:	not determined

Self-ignition temperature

Solid:	No data available
Gas:	No data available

Decomposition temperature: No data available

pH-Value: not applicable

Viscosity / kinematic: 14,5 mm²/s ASTM D 7042
(at 100 °C)

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: No data available

Vapour pressure: No data available

Density (at 15 °C): 0,861 g/cm³ DIN 51757

Relative vapour density: No data available

9.2. Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 8 of 13

Oxidizing properties
No data available

Evaporation rate: No data available

Further Information
No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with :Oxidizing agents, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides.
Nitrogen oxides (NO_x). carbon black

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.
Mixture not tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
36878-20-3	Bis(nonylphenyl)amine				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1981)	OECD Guideline 401
121158-58-5	phenol, dodecyl-, branched				
	oral	LD50 2100 mg/kg	Rat	Publication (1978)	OECD Guideline 401
	dermal	LD50 ca. 15000 mg/kg	Rabbit	Study report (1968)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposureBased on available data, the classification criteria are not met.
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.**Aspiration hazard**

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

No data available

Mixture not tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h			
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
36878-20-3	Bis(nonylphenyl)amine					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2019)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202
	Crustacea toxicity	NOEC 4,45 mg/l	21 d	Daphnia magna	Study report (2019)	OECD Guideline 211
121158-58-5	phenol, dodecyl-, branched					
	Acute fish toxicity	LL50 40 mg/l	96 h	Pimephales promelas	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 0,15 mg/l	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,037 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,004 mg/l	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 > 1000 mg/l)	3 h	activated sludge of a predominantly industrial sew	Study report (2004)	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
36878-20-3	Bis(nonylphenyl)amine	11,87
121158-58-5	phenol, dodecyl-, branched	7,14

BCF

CAS No	Chemical name	BCF	Species	Source
36878-20-3	Bis(nonylphenyl)amine	411	Cyprinus carpio	Study report (2000)
121158-58-5	phenol, dodecyl-, branched	289	Oncorhynchus mykiss	Study report (2006)

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 11 of 13

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 12 of 13

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

phenol, dodecyl-, branched

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 30

National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,4,6,7,9,11,12,15,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 17.11.2022

Product code: 722180

Page 13 of 13

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)