



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**ADDINOL Super Diesel MD 1545**

Revision date: 24.01.2019

Product code: 722006

Page 2 of 8

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 3 of 8

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

#### **6.4. Reference to other sections**

Refer to the provisions listed in Sections 8, 12 and 13.

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eye and clothing.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place.

##### **Advice on storage compatibility**

Keep away from food, drink and animal feedingstuffs.  
Keep away from: Oxidizing agents.

##### **Further information on storage conditions**

Recommended storage temperature: 5 - 40°C  
Protect against: heat, UV-radiation/sunlight, frost.

#### **7.3. Specific end use(s)**

Motor oil. Further information: see technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### **8.1. Control parameters**

##### **Additional advice on limit values**

Recommended limit value for oil mist  
TWA: 5 mg/m<sup>3</sup>  
STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### **8.2. Exposure controls**



##### **Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

##### **Protective and hygiene measures**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

##### **Eye/face protection**

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 4 of 8

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow - brown
Odour:	like: mineral oil.

#### Test method

pH-Value: No data available

#### Changes in the physical state

Melting point: No data available

Initial boiling point and boiling range: not determined

Pour point: -40 °C ASTM D 7346

Flash point: 230 °C DIN EN ISO 2592

#### Flammability

Solid: No data available

Gas: No data available

#### Explosive properties

No data available

Lower explosion limits: No data available

Upper explosion limits: No data available

Ignition temperature: not determined

#### Auto-ignition temperature

Solid: No data available

Gas: No data available

Decomposition temperature: No data available

#### Oxidizing properties

No data available

Vapour pressure: No data available

Density (at 15 °C): 0,870 g/cm<sup>3</sup> DIN 51757

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 5 of 8

Water solubility:	virtually insoluble
<b>Solubility in other solvents</b>	
No data available	
Partition coefficient:	No data available
Viscosity / kinematic: (at 100 °C)	14,0 mm <sup>2</sup> /s ASTM D 7042
Vapour density:	No data available
Evaporation rate:	No data available

#### **9.2. Other information**

No data available

### SECTION 10: Stability and reactivity

#### **10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

#### **10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature.

#### **10.3. Possibility of hazardous reactions**

No known hazardous reactions.

#### **10.4. Conditions to avoid**

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

#### **10.5. Incompatible materials**

Reacts with : Oxidizing agents, strong. Reducing agents.

#### **10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

### SECTION 11: Toxicological information

#### **11.1. Information on toxicological effects**

##### **Acute toxicity**

No data available

Mixture not tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		

##### **Irritation and corrosivity**

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

##### **Carcinogenic/mutagenic/toxic effects for reproduction**

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 6 of 8

**STOT-repeated exposure**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Specific effects in experiment on an animal**

No data available

## SECTION 12: Ecological information

**12.1. Toxicity**

No data available

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LC50 mg/l	>1.000	96 h		
	Acute algae toxicity	ErC50 mg/l	>100	72 h		

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

**12.6. Other adverse effects**

No data available

**Further information**

Do not allow uncontrolled leakage of product into the environment.

## SECTION 13: Disposal considerations

**13.1. Waste treatment methods****Advice on disposal**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**Waste disposal number of waste from residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

## SECTION 14: Transport information

**Land transport (ADR/RID)**

**14.1. UN number:** -

**14.2. UN proper shipping name:** -

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 7 of 8

**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Inland waterways transport (ADN)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Marine transport (IMDG)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**Other applicable information**

No dangerous good in sense of these transport regulations.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,8,9,10,11,12,14,15.

**Relevant H and EUH statements (number and full text)**

H304 May be fatal if swallowed and enters airways.

EUH210 Safety data sheet available on request.

**Further Information**

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [GHS].

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Super Diesel MD 1545**

Revision date: 24.01.2019

Product code: 722006

Page 8 of 8

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*