

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 2 of 8

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 3 of 8

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eye and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place.

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.
Keep away from: Oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C
Protect against: heat, UV-radiation/sunlight, frost.

7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Recommended limit value for oil mist
TWA: 5 mg/m³
STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 4 of 8

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow - brown
Odour:	like: mineral oil.

Test method

pH-Value: No data available

Changes in the physical state

Melting point: No data available

Initial boiling point and boiling range: not determined

Pour point: -40 °C ASTM D 7346

Flash point: 230 °C DIN EN ISO 2592

Flammability

Solid: No data available

Gas: No data available

Explosive properties

No data available

Lower explosion limits: No data available

Upper explosion limits: No data available

Ignition temperature: not determined

Auto-ignition temperature

Solid: No data available

Gas: No data available

Decomposition temperature: No data available

Oxidizing properties

No data available

Vapour pressure: No data available

Density (at 15 °C): 0,870 g/cm³ DIN 51757

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 5 of 8

Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient:	No data available
Viscosity / kinematic: (at 100 °C)	14,0 mm ² /s ASTM D 7042
Vapour density:	No data available
Evaporation rate:	No data available

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with : Oxidizing agents, strong. Reducing agents.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No data available

Mixture not tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		

Irritation and corrosivity

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 6 of 8

STOT-repeated exposure

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Specific effects in experiment on an animal

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LC50 mg/l	>1.000	96 h		
	Acute algae toxicity	ErC50 mg/l	>100	72 h		

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods**Advice on disposal**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

Waste disposal number of waste from residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: -

14.2. UN proper shipping name: -

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 7 of 8

14.3. Transport hazard class(es): -**14.4. Packing group:** -**Inland waterways transport (ADN)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Marine transport (IMDG)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,8,9,10,11,12,14,15.

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

EUH210 Safety data sheet available on request.

Further Information

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [GHS].

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Diesel MD 1545

Revision date: 24.01.2019

Product code: 722006

Page 8 of 8

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)