

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Eco Gas 4205 XD**

Revision date: 23.06.2022

Product code: 725033

Page 1 of 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

ADDINOL Eco Gas 4205 XD

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Motor oil.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

|                         |                                |                               |
|-------------------------|--------------------------------|-------------------------------|
| Company name:           | ADDINOL Lube Oil GmbH          |                               |
|                         | Gebäude 4609                   |                               |
| Street:                 | Am Haupttor                    |                               |
| Place:                  | D-06237 Leuna                  |                               |
| Telephone:              | +49 (0) 3461 845-0             | Telefax: +49 (0) 3461 845-555 |
| e-mail:                 | info@addinol.de                |                               |
| Contact person:         | Application Technology         |                               |
| Internet:               | www.addinol.de                 |                               |
| Responsible Department: | ADDINOL Application Technology |                               |

**Supplier**

|                 |                                 |                            |
|-----------------|---------------------------------|----------------------------|
| Company name:   | GEM OILS LIMITED                |                            |
| Place:          | IRL-H12 E4W2 Regaskin Co. Cavan |                            |
| Telephone:      | +353 49 4378116                 | Telefax: +353 49 4368329   |
| e-mail:         | sales@gemoils.ie                |                            |
| Contact person: | GEM OILS LIMITED                | Telephone: +353 49 4378116 |
| e-mail:         | sales@gemoils.ie                |                            |
| Internet:       | https://gemoils.ie/             |                            |

**1.4. Emergency telephone number:**

Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

**2.2. Label elements****Regulation (EC) No 1272/2008****Special labelling of certain mixtures**

|        |   |
|--------|---|
| EUH208 | Contains Benzenesulfonic acid, propenated, calcium salt, overbased. May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request.   |

**Additional advice on labelling**

According to EC directives or the corresponding national regulations the product does not have to be labelled.

**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
Spilled product must not leak into the ground.  
Do not allow uncontrolled leakage of product into the environment.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Eco Gas 4205 XD**

Revision date: 23.06.2022

Product code: 725033

Page 2 of 11

**Hazardous components**

| CAS No      | Chemical name   |              |                  | Quantity      |
|-------------|---|--------------|------------------|---------------|
|             | EC No   | Index No     | REACH No         |               |
|             | Classification (Regulation (EC) No 1272/2008)   |              |                  |               |
| 64742-54-7  | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified           |              |                  | 80 - < 100 %  |
|             | 265-157-1   |              | 01-2119484627-25 |               |
|             | Asp. Tox. 1; H304   |              |                  |               |
| 125643-61-0 | reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate |              |                  | 2.5 - < 5 %   |
|             | 406-040-9   | 607-530-00-7 |                  |               |
|             | Aquatic Chronic 4; H413   |              |                  |               |
| 68610-84-4  | Benzenesulfonic acid, propenated, calcium salt, overbased                               |              |                  | 0.3 - < 0.5 % |
|             | 271-877-7   |              |                  |               |
|             | Skin Sens. 1, Aquatic Chronic 4; H317 H413  |              |                  |               |

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

| CAS No      | EC No     | Chemical name   | Quantity     |
|-------------|-----------|---|--------------|
|             |           | Specific Conc. Limits, M-factors and ATE  |              |
| 64742-54-7  | 265-157-1 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified           | 80 - < 100 % |
|             |           | dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg                                  |              |
| 125643-61-0 | 406-040-9 | reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate | 2.5 - < 5 %  |
|             |           | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg                                  |              |

**Further Information**

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

DMSO-Extrakt < 3 %, IP 346.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ADDINOL Eco Gas 4205 XD

Revision date: 23.06.2022

Product code: 725033

Page 3 of 11

First Aid, decontamination, treatment of symptoms.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

##### **Unsuitable extinguishing media**

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.3. Methods and material for containment and cleaning up

##### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

##### **Advice on general occupational hygiene**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Eco Gas 4205 XD

Revision date: 23.06.2022

Product code: 725033

Page 4 of 11

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.  
Keep away from: Oxidizing agents.

#### Further information on storage conditions

Recommended storage temperature: 5 - 40°C  
Protect against: heat. UV-radiation/sunlight. frost.

#### 7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### DNEL/DMEL values

| CAS No      | Substance   | Exposure route | Effect   | Value                  |
|-------------|---|----------------|----------|------------------------|
| 64742-54-7  | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified           |                |          |                        |
|             | Worker DNEL, long-term  | inhalation     | systemic | 2,73 mg/m <sup>3</sup> |
|             | Worker DNEL, long-term  | inhalation     | local    | 5,58 mg/m <sup>3</sup> |
|             | Worker DNEL, long-term  | dermal         | systemic | 0,97 mg/kg bw/day      |
|             | Consumer DNEL, long-term  | inhalation     | local    | 1,19 mg/m <sup>3</sup> |
|             | Consumer DNEL, long-term  | oral           | systemic | 0,74 mg/kg bw/day      |
| 125643-61-0 | reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate |                |          |                        |
|             | Worker DNEL, long-term  | inhalation     | systemic | 6,6 mg/m <sup>3</sup>  |
|             | Worker DNEL, long-term  | dermal         | systemic | 1,67 mg/kg bw/day      |
|             | Consumer DNEL, long-term  | inhalation     | systemic | 1,62 mg/m <sup>3</sup> |
|             | Consumer DNEL, long-term  | dermal         | systemic | 0,83 mg/kg bw/day      |
|             | Consumer DNEL, long-term  | oral           | systemic | 0,93 mg/kg bw/day      |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Eco Gas 4205 XD**

Revision date: 23.06.2022

Product code: 725033

Page 5 of 11

**PNEC values**

| CAS No      | Substance   |             |
|-------------|---|-------------|
|             | Environmental compartment   | Value       |
| 64742-54-7  | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified           |             |
|             | Secondary poisoning   | 9,33 mg/kg  |
| 125643-61-0 | reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate |             |
|             | Freshwater  | 0,018 mg/l  |
|             | Freshwater (intermittent releases)  | 0,018 mg/l  |
|             | Marine water  | 0,002 mg/l  |
|             | Freshwater sediment   | 2 mg/kg     |
|             | Marine sediment   | 0,2 mg/kg   |
|             | Secondary poisoning   | 41,33 mg/kg |
|             | Micro-organisms in sewage treatment plants (STP)  | 100 mg/l    |
|             | Soil  | 10 mg/kg    |

**Additional advice on limit values**

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

**Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

**Skin protection**

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fuchphointe &gt; 65 ° C: A1:

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Eco Gas 4205 XD**

Revision date: 23.06.2022

Product code: 725033

Page 6 of 11

&lt;1000 ppm; A2: &lt;5000 ppm; A3: &lt;10,000 ppm.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: liquid  
 Colour: yellow - brown  
 Odour: characteristic

**Test method****Changes in the physical state**

Melting point/freezing point: No data available  
 Boiling point or initial boiling point and boiling range: No data available  
 Pour point: -21 °C ASTM D 7346  
 Flash point: 286 °C DIN EN ISO 2592

**Flammability**

Solid/liquid: No data available  
 Gas: No data available

**Explosive properties**

No data available

Lower explosion limits: No data available

Upper explosion limits: No data available

Auto-ignition temperature: No data available

**Self-ignition temperature**

Solid: not determined  
 Gas: not determined

Decomposition temperature: not determined

pH-Value: not applicable

Viscosity / kinematic: 12,8 mm<sup>2</sup>/s ASTM D 7042  
(at 100 °C)

Water solubility: virtually insoluble

**Solubility in other solvents**

No data available

Partition coefficient n-octanol/water: No data available

Vapour pressure: not determined

Density (at 15 °C): 0,876 g/cm<sup>3</sup> DIN 51757

Relative vapour density: No data available

**9.2. Other information**

Oxidizing properties  
 No data available

Evaporation rate: No data available

**Further Information**

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Eco Gas 4205 XD

Revision date: 23.06.2022

Product code: 725033

Page 7 of 11

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

##### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

##### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

##### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

##### 10.5. Incompatible materials

Reacts with : Oxidizing agents, strong.

##### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

#### SECTION 11: Toxicological information

##### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

###### Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

| CAS No      | Chemical name   |                   |         |                     |                    |
|-------------|---|-------------------|---------|---------------------|--------------------|
|             | Exposure route  | Dose              | Species | Source              | Method             |
| 64742-54-7  | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified           |                   |         |                     |                    |
|             | oral  | LD50 > 5000 mg/kg | Rat     | Study report (1982) | OECD Guideline 401 |
|             | dermal  | LD50 > 5000 mg/kg | Rabbit  | Study report (1982) | OECD Guideline 402 |
| 125643-61-0 | reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate |                   |         |                     |                    |
|             | oral  | LD50 > 2000 mg/kg | Rat     | Study report (2005) | OECD Guideline 423 |
|             | dermal  | LD50 > 2000 mg/kg | Rat     | Study report (2000) | OECD Guideline 402 |

###### Irritation and corrosivity

Based on available data, the classification criteria are not met.

###### Sensitising effects

Contains Benzenesulfonic acid, propenated, calcium salt, overbased. May produce an allergic reaction.

###### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

###### STOT-single exposure

Based on available data, the classification criteria are not met.

###### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Eco Gas 4205 XD

Revision date: 23.06.2022

Product code: 725033

Page 8 of 11

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable

## SECTION 12: Ecological information

**12.1. Toxicity**

| CAS No      | Chemical name   |                    |           |   |                                   |   |
|-------------|---|--------------------|-----------|---|-----------------------------------|---|
|             | Aquatic toxicity  | Dose               | [h]   [d] | Species   | Source                            | Method                                  |
| 64742-54-7  | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified           |                    |           |   |                                   |   |
|             | Acute fish toxicity   | LL50 > 100 mg/l    | 96 h      | Pimephales promelas                                 | Study report (1995)               | OECD Guideline 203                      |
|             | Acute algae toxicity  | ErC50 >100 mg/l    | 72 h      |   |                                   |   |
|             | Fish toxicity   | NOEC >= 1000 mg/l  | 14 d      | Oncorhynchus mykiss                                 | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a |
| 125643-61-0 | reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate |                    |           |   |                                   |   |
|             | Acute fish toxicity   | LC50 > 0,001 mg/l  | 96 h      | Oncorhynchus mykiss                                 | Study report (2009)               | OECD Guideline 203                      |
|             | Acute algae toxicity  | ErC50 > 0 mg/l     | 72 h      | Desmodesmus subspicatus                             | Study report (2009)               | OECD Guideline 201                      |
|             | Acute crustacea toxicity  | EL50 110 mg/l      | 48 h      | Daphnia magna                                       | Study report (2000)               | OECD Guideline 202                      |
|             | Fish toxicity   | NOEC 0,36 mg/l     | 33 d      | Pimephales promelas                                 | Study report (2009)               | OECD Guideline 210                      |
|             | Crustacea toxicity  | NOEC 3,2 mg/l      | 21 d      | Daphnia magna                                       | Study report (2010)               | OECD Guideline 211                      |
|             | Acute bacteria toxicity   | (EC50 > 1000 mg/l) | 3 h       | activated sludge of a predominantly domestic sewage | Study report (2000)               | OECD Guideline 209                      |

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

| CAS No      | Chemical name   | Log Pow  |
|-------------|---|----------|
| 125643-61-0 | reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate | 15100000 |

**BCF**

| CAS No      | Chemical name   | BCF | Species         | Source              |
|-------------|---|-----|-----------------|---------------------|
| 125643-61-0 | reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate | 38  | Cyprinus carpio | Study report (2002) |

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Eco Gas 4205 XD**

Revision date: 23.06.2022

Product code: 725033

Page 9 of 11

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

not applicable

**12.7. Other adverse effects**

No data available

**Further information**

Do not allow uncontrolled leakage of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**List of Wastes Code - residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Marine transport (IMDG)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Maritime transport in bulk according to IMO instruments**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Eco Gas 4205 XD**

Revision date: 23.06.2022

Product code: 725033

Page 10 of 11

not applicable

**Other applicable information**

No dangerous good in sense of these transport regulations.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Relevant H and EUH statements (number and full text)**

|        |   |
|--------|---|
| H304   | May be fatal if swallowed and enters airways.   |
| H317   | May cause an allergic skin reaction.  |
| H413   | May cause long lasting harmful effects to aquatic life.   |
| EUH208 | Contains Benzenesulfonic acid, propenated, calcium salt, overbased. May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request.   |

**Further Information**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Eco Gas 4205 XD**

Revision date: 23.06.2022

Product code: 725033

Page 11 of 11

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*