according to Regulation (EC) No 1907/2006

### **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

ADDINOL Penta-Fluid DW 08

UFI: 5QMS-D6GA-W205-WYA5

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Corrosion inhibitor.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

**Supplier** 

Company name: Specialised Products (Western) Limited
Street: 76 Cobham Road, Ferndown Industrial Estate,

Place: GB-BH21 7RN Wimborne, Dorset

Telephone: +44 1202 891393 Telefax: +44 1202 876908

e-mail: sales@specialisedproducts.co.uk
Internet: http://specialisedproducts.co.uk

**1.4. Emergency telephone** +44 1202 891393 - This number is serviced during office hours.

number:

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Regulation (EC) No. 1272/2008

Hazard categories:

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

May be fatal if swallowed and enters airways.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# 2.2. Label elements

# Regulation (EC) No. 1272/2008

# Hazard components for labelling

Distillates (petroleum), hydrotreated light naphthenic

Signal word: Danger

Pictograms:



### **Hazard statements**

H304 May be fatal if swallowed and enters airways.

according to Regulation (EC) No 1907/2006

### **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 2 of 12

### **Precautionary statements**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to industrial incineration plant.

# Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

# Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

# 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Do not allow uncontrolled leakage of product into the environment.

Harmful if swallowed.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
64742-53-6	Distillates (petroleum), hydrotreated	l light naphthenic		60 - 80 %	
	265-156-6		01-2119480375-34		
	Asp. Tox. 1; H304				
68603-10-1	Barium salt of organic acids		< 5 %		
	271-637-1				
	Acute Tox. 4, Acute Tox. 4; H332 H				
111-76-2	Butylglycole			< 5 %	
	203-905-0				
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H311 H302 H315 H319				

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

opecine con	C. Ellillis, Wi-lac	tors and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
64742-53-6	265-156-6	Distillates (petroleum), hydrotreated light naphthenic	60 - 80 %
	dermal: LD50 =	= > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
68603-10-1	271-637-1	Barium salt of organic acids	< 5 %
	inhalation: ATE	= 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: ATE = 500	
111-76-2	203-905-0	Butylglycole	< 5 %
		i0 = 523 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 g; oral: LD50 = 1414 mg/kg	

### **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

### **SECTION 4: First aid measures**

according to Regulation (EC) No 1907/2006

### **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 3 of 12

### 4.1. Description of first aid measures

#### General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eves

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Seek medical attention if problems persist.

### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

# 4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Coughing, difficulties of breathing.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx), carbon black.

# 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

# Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### **General measures**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

# 6.3. Methods and material for containment and cleaning up

### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

according to Regulation (EC) No 1907/2006

### **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 4 of 12

### 6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Provide adequate ventilation. When hot, product develops flammable vapours.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

# Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

# Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: UV-radiation/sunlight. frost. heat. Recommended storage temperature: 5 - 40°C

## 7.3. Specific end use(s)

Further information: see technical data sheet.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL

# **Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol		Post shift

according to Regulation (EC) No 1907/2006

# **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 5 of 12

# **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic					
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³		
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³		
Worker DNEL,	long-term	dermal	systemic	0,97 mg/kg bw/day		
Consumer DNI	EL, long-term	inhalation	local	1,19 mg/m³		
Consumer DNI	EL, long-term	oral	systemic	0,74 mg/kg bw/day		
68603-10-1	Barium salt of organic acids					
Worker DNEL,	long-term	inhalation	systemic	0,23 mg/m³		
Worker DNEL,	long-term	dermal	systemic	1,7 mg/kg bw/day		
Consumer DNI	EL, long-term	inhalation	systemic	0,06 mg/m³		
Consumer DNI	EL, long-term	dermal	systemic	0,8 mg/kg bw/day		
Consumer DNI	EL, long-term	oral	systemic	0,8 mg/kg bw/day		
111-76-2	Butylglycole					
Worker DNEL,	acute	inhalation	systemic	1091 mg/m³		
Worker DNEL,	acute	inhalation	local	246 mg/m³		
Consumer DNI	EL, long-term	inhalation	systemic	59 mg/m³		
Consumer DNI	EL, acute	inhalation	systemic	426 mg/m³		
Consumer DNEL, acute		inhalation	local	147 mg/m³		
Consumer DNEL, long-term		oral	systemic	6,3 mg/kg bw/day		
Consumer DNEL, acute		oral	systemic	26,7 mg/kg bw/day		
Worker DNEL, long-term		dermal	systemic	75 mg/kg bw/day		
Worker DNEL,	long-term	inhalation	systemic	98 mg/m³		

according to Regulation (EC) No 1907/2006

# **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 6 of 12

### **PNEC values**

01011			
CAS No	Substance		
Environmental	Environmental compartment		
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic		
Secondary poi	soning	9,33 mg/kg	
68603-10-1	Barium salt of organic acids		
Freshwater		0,1 mg/l	
Freshwater (in	termittent releases)	1 mg/l	
Marine water		0,01 mg/l	
Freshwater se	diment	4270 mg/kg	
Marine sediment		427 mg/kg	
Secondary poisoning		66,7 mg/kg	
Micro-organisms in sewage treatment plants (STP)		100 mg/l	
Soil 854 mg		854 mg/kg	
111-76-2	Butylglycole		
Freshwater		8,8 mg/l	
Freshwater (intermittent releases)		26,4 mg/l	
Marine water		0,88 mg/l	
Freshwater sediment		34,6 mg/kg	
Marine sediment		3,46 mg/kg	
Secondary poisoning 20 mg/l		20 mg/kg	
Micro-organisms in sewage treatment plants (STP)  463 mg/l		463 mg/l	
Soil		2,33 mg/kg	

# Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

# 8.2. Exposure controls





# Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

# Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

# **Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

according to Regulation (EC) No 1907/2006

# **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 7 of 12

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: brown

Odour: like: mineral oil.

Test method

pH-Value: not applicable

Changes in the physical state

Melting point:

No data available
Boiling point or initial boiling point and

200 °C

boiling range:

Flash point: 130 °C DIN EN ISO 2592

Flammability

Solid/liquid: No data available
Gas: No data available

**Explosive properties** 

No data available

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 6,5 vol. %
Auto-ignition temperature: > 220 °C

Self-ignition temperature

Solid: No data available
Gas: No data available
Decomposition temperature: No data available

**Oxidizing properties** 

No data available

Vapour pressure: No data available

Density (at 15 °C): 0,88 g/cm³ DIN EN ISO 12185

Water solubility: insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: No data available

according to Regulation (EC) No 1907/2006

# **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 8 of 12

Viscosity / kinematic: 8 mm²/s DIN EN ISO 3104

(at 40 °C)

Relative vapour density:

Evaporation rate:

No data available

No data available

# 9.2. Other information

No data available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

# 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

# 10.3. Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

### 10.5. Incompatible materials

Reacts with: Oxidizing agents, strong.

# 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

according to Regulation (EC) No 1907/2006

### **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 9 of 12

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64742-53-6	Distillates (petroleum), h	ydrotreated	light naphthe	nic				
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402		
68603-10-1	Barium salt of organic acids							
	oral	ATE mg/kg	500					
	inhalation vapour	ATE	11 mg/l					
	inhalation aerosol	ATE	1,5 mg/l					
111-76-2	Butylglycole							
	oral	LD50 mg/kg	1414	Guinea pig	Study report (1994)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1993)	OECD Guideline 402		
	inhalation (4 h) vapour	LC50	523 mg/l	Rat	Study report (1980)	OECD Guideline 403		
_	inhalation aerosol	ATE	0,5 mg/l					

# Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

# **Aspiration hazard**

May be fatal if swallowed and enters airways.

# 11.2. Information on other hazards

# **Endocrine disrupting properties**

not applicable

# **Further information**

Toxicological data are not available.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

according to Regulation (EC) No 1907/2006

# **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 10 of 12

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64742-53-6	Distillates (petroleum), hy	drotreated I	ight naphther	nic				
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> 100					
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
68603-10-1	Barium salt of organic aci	ds						
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Oncorhynchus mykiss	Study report (2012)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2012)	OECD Guideline 201	
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	Study report (2012)	OECD Guideline 202	
	Acute bacteria toxicity	(> 1000	mg/l)	3 h	activated sludge of a predominantly domestic sewag	Study report (2012)	OECD Guideline 209	
111-76-2	Butylglycole							
	Acute fish toxicity	LC50 mg/l	1474	96 h	Oncorhynchus mykiss	Toxicol Mech Meth 12, 255-63 (2002)	OECD Guideline 203	
	Acute algae toxicity	ErC50	911 mg/l	72 h	Pseudokirchneriella subcapitata	Toxicol Mech Meth 12, 255-63 (2002)	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	1550	48 h	Daphnia magna	Toxicol Mech Meth 12, 255-63 (2002)	OECD Guideline 202	
	Fish toxicity	NOEC mg/l	> 100	21 d	Danio rerio	Toxicol Mech Meth 12, 255-63 (2002)	OECD Guideline 204	
	Crustacea toxicity	NOEC	100 mg/l	21 d	Daphnia magna	Toxicol Mech Meth 12, 255-63 (2002)	OECD Guideline 211	

# 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

# 12.3. Bioaccumulative potential

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68603-10-1	Barium salt of organic acids	> 10000000000
111-76-2	Butylglycole	0,81

# 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

# 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No data available

## **Further information**

Do not allow uncontrolled leakage of product into the environment.

according to Regulation (EC) No 1907/2006

#### **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 11 of 12

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

### List of Wastes Code - residues/unused products

120107

WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

# **SECTION 14: Transport information**

<u>14.1. UN number:</u>

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number: -

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG)

<u>14.1. UN number:</u> -

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group: -

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u> -

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### Other applicable information

No dangerous good in sense of these transport regulations.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No 1907/2006

### **ADDINOL Penta-Fluid DW 08**

Revision date: 09.06.2021 Product code: 770044 Page 12 of 12

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

# National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,7,8,9,11,12,15,16.

### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

# Relevant H and EUH statements (number and full text)

,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Classification procedure			
Asp. Tox. 1; H304	Calculation method			
Polovent H and EIIH statements (number and full toxt)				

#### Harmful if swallowed. H302

H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
11000	

H332 Harmful if inhaled.

**EUH066** Repeated exposure may cause skin dryness or cracking.

# **Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)