according to UK REACH Regulation

# **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 1 of 11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

ADDINOL Hydraulic Oil HVLPD 68

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hydraulic fluid(s) and filler(s).

#### 1.3. Details of the supplier of the safety data sheet

| Manufacturer |
|--------------|
|--------------|

| Company name:            | ADDINOL Lube Oil GmbH<br>Gebäude 4609       |                               |
|--------------------------|---|-------------------------------|
| Street:                  | Am Haupttor                                 |                               |
| Place:                   | D-06237 Leuna                               |                               |
| Telephone:               | +49 (0) 3461 845-0                          | Telefax: +49 (0) 3461 845-555 |
| E-mail:                  | info@addinol.de                             |                               |
| Contact person:          | Application Technology                      |                               |
| Internet:                | www.addinol.de                              |                               |
| Responsible Department:  | ADDINOL Application Technology              |                               |
| Supplier                 |   |                               |
| Company name:            | Gidov Oil & Logistics Ltd.                  |                               |
| Street:                  | 76 Cobham Road, Ferndown Industrial Estate  |                               |
| Place:                   | GB-TN157DA Wrotham, Sevenoaks Kent          |                               |
| Telephone:               | +44 7729229830                              | Telefax: +44 7729229830       |
| E-mail:                  | sales@addinol.co.uk                         |                               |
| Internet:                | https://www.gidovlogistics.co.uk/           |                               |
| 1.4. Emergency telephone | +44 7729229830 - This number is serviced du | ring office hours.            |
|                          |   |                               |

### number:

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

## 2.2. Label elements

#### **GB CLP Regulation**

#### Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

#### Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

# 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Spilled product must not leak into the ground. Do not allow uncontrolled leakage of product into the environment.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

according to UK REACH Regulation

# **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 2 of 11

#### **Relevant ingredients**

| CAS No     | Chemical name  |                   |                  |              |  |
|------------|--|-------------------|------------------|--------------|--|
|            | EC No  | Index No          | REACH No         |              |  |
|            | Classification (GB CLP Regulation)   |                   |                  |              |  |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic                           |                   |                  | 80 - < 100 % |  |
|            | 265-157-1  |                   | 01-2119484627-25 |              |  |
|            | Asp. Tox. 1; H304  |                   |                  |              |  |
|            | Reaction products of bis(4-methylpopping) propylene oxide and amines, C12-1      | phosphorus oxide, | 0.1 - < 0.3 %    |              |  |
|            | 931-384-6  | 01-2119493620-38  |                  |              |  |
|            | Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H302 H319 H317 H411 |                   |                  |              |  |

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

| CAS No     | EC No  | Chemical name   | Quantity      |  |  |
|------------|--|---|---------------|--|--|
|            | Specific Conc. I                                       | imits, M-factors and ATE  |               |  |  |
| 64742-54-7 | 265-157-1  | Distillates (petroleum), hydrotreated heavy paraffinic  | 80 - < 100 %  |  |  |
|            | dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg |   |               |  |  |
|            |  | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | 0.1 - < 0.3 % |  |  |
|            | dermal: LD50 =<br>Sens. 1; H317:                       | = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 Skin<br>>= 9,39 - 100   |               |  |  |

#### **Further Information**

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

Give activated carbon, in order to reduce the resorption in the gastro-enteric tract. Call a physician immediately.

### **4.2. Most important symptoms and effects, both acute and delayed** The following symptoms may occur: Coughing. difficulties of breathing.

### **4.3. Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

according to UK REACH Regulation

# **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 3 of 11

#### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water. Sand.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). phosphorus oxides. Sulfur oxides. carbon black.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

# 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory) Disposal: see section 13

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Provide adequate ventilation. When hot, product develops flammable vapours.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

## 7.2. Conditions for safe storage, including any incompatibilities

according to UK REACH Regulation

## **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 4 of 11

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

# Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Oxidizing agent

# Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 5 - 40°C

# 7.3. Specific end use(s)

Further information: see technical data sheet.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### DNEL/DMEL values

| CAS No                   | Substance  |                          |                        |                        |
|--------------------------|--|--------------------------|------------------------|------------------------|
| DNEL type                |  | Exposure route           | Effect                 | Value                  |
| 64742-54-7               | Distillates (petroleum), hydrotreated heavy paraffinic                                     |                          |                        |                        |
| Worker DNEL,             | long-term  | inhalation               | systemic               | 2,73 mg/m³             |
| Worker DNEL,             | long-term  | inhalation               | local                  | 5,58 mg/m³             |
| Worker DNEL,             | long-term  | dermal                   | systemic               | 0,97 mg/kg<br>bw/day   |
| Consumer DN              | EL, long-term  | inhalation               | local                  | 1,19 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |  | oral                     | systemic               | 0,74 mg/kg<br>bw/day   |
|                          | Reaction products of bis(4-methylpentan-2-yl)dithiophospheramines, C12-14-alkyl (branched) | pric acid with phosphore | us oxide, propylene ox | ide and                |
| Worker DNEL,             | long-term  | inhalation               | systemic               | 4,28 mg/m <sup>3</sup> |
| Worker DNEL,             | long-term  | dermal                   | systemic               | 12,5 mg/kg<br>bw/day   |
| Consumer DN              | EL, long-term  | inhalation               | systemic               | 1,09 mg/m³             |
| Consumer DNI             | EL, long-term  | dermal                   | systemic               | 6,25 mg/kg<br>bw/day   |
| Consumer DN              | EL, long-term  | oral                     | systemic               | 0,25 mg/kg<br>bw/day   |

according to UK REACH Regulation

# **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 5 of 11

### **PNEC** values

| CAS No         | Substance  |                  |  |  |  |  |
|----------------|--|------------------|--|--|--|--|
| Environmenta   | l compartment  | Value            |  |  |  |  |
| 64742-54-7     | Distillates (petroleum), hydrotreated heavy paraffinic   |                  |  |  |  |  |
| Secondary po   | isoning  | 9,33 mg/kg       |  |  |  |  |
|                | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, pro<br>amines, C12-14-alkyl (branched) | pylene oxide and |  |  |  |  |
| Freshwater     |  | 0,0024 mg/l      |  |  |  |  |
| Freshwater (ir | ntermittent releases)  | 0,15 mg/l        |  |  |  |  |
| Marine water   |  | 0,00024 mg/l     |  |  |  |  |
| Freshwater se  | ediment  | 0,0129 mg/kg     |  |  |  |  |
| Marine sedim   | ent  | 0,00129 mg/kg    |  |  |  |  |
| Secondary po   | isoning  | 10 mg/kg         |  |  |  |  |
| Micro-organis  | ms in sewage treatment plants (STP)  | 24,33 mg/l       |  |  |  |  |
| Soil           |  | 0,00117 mg/kg    |  |  |  |  |

# Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

## 8.2. Exposure controls





### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374. Breakthrough times and swelling properties of the material must be taken into consideration.

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

according to UK REACH Regulation

## **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 6 of 11

### **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point >  $65^{\circ}$ C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

| 9.1. Information on basic physical and chen |                    |                         |                 |
|---|--------------------|-------------------------|-----------------|
| Physical state:                             | liquid             |                         |                 |
| Colour:                                     | yellow             |                         |                 |
| Odour:                                      | like: mineral oil. |                         |                 |
| Odour threshold:                            | not determined     |                         |                 |
|   |                    |                         | Test method     |
| Melting point/freezing point:               |                    | No data available       |                 |
| Boiling point or initial boiling point and  |                    | not determined          |                 |
| boiling range:                              |                    |                         |                 |
| Flammability:                               |                    | No data available       |                 |
| Lower explosion limits:                     |                    | No data available       |                 |
| Upper explosion limits:                     |                    | No data available       |                 |
| Flash point:                                |                    | 238 °C                  | DIN EN ISO 2592 |
| Auto-ignition temperature:                  |                    | not determined          | DIN 51794       |
| Decomposition temperature:                  |                    | No data available       |                 |
| pH-Value:                                   |                    | not applicable          |                 |
| Viscosity / kinematic:                      |                    | 67,8 mm²/s              | ASTM D 7042     |
| (at 40 °C)                                  |                    |                         |                 |
| Water solubility:                           |                    | virtually insoluble     |                 |
| Solubility in other solvents                |                    |                         |                 |
| No data available                           |                    |                         |                 |
| Partition coefficient n-octanol/water:      |                    | No data available       |                 |
| Vapour pressure:                            |                    | No data available       |                 |
| Density (at 15 °C):                         |                    | 0,867 g/cm <sup>3</sup> | DIN 51757       |
| Relative vapour density:                    |                    | No data available       |                 |
| Particle characteristics:                   |                    | No data available       |                 |
| 9.2. Other information                      |                    |                         |                 |
| Information with regard to physical haza    | rd classes         |                         |                 |
| Explosive properties                        |                    |                         |                 |
| No data available                           |                    |                         |                 |
| Self-ignition temperature                   |                    |                         |                 |
| Solid:                                      |                    | No data available       |                 |
| Gas:  |                    | No data available       |                 |
| Oxidizing properties                        |                    |                         |                 |
| No data available                           |                    |                         |                 |
| Other safety characteristics                |                    |                         |                 |
| Evaporation rate:                           |                    | No data available       |                 |
| Pour point:                                 |                    | -36 °C                  | ASTM D 7346     |
| SECTION 40, Stobility and reactivity        |                    |                         |                 |
| SECTION 10: Stability and reactivity        |                    |                         |                 |

## 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

# 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

according to UK REACH Regulation

# **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 7 of 11

## 10.3. Possibility of hazardous reactions

No known hazardous reactions.

## 10.4. Conditions to avoid

Do not overheat to avoid decomposition by heat.

Refer to chapter 7 No further action is necessary.

### 10.5. Incompatible materials

Reacts with: Oxidizing agents, strong.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). phosphorus oxides. Sulfur oxides. carbon black.

### **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No     | Chemical name   |               |                |         |                     |                    |  |  |
|------------|---|---------------|----------------|---------|---------------------|--------------------|--|--|
|            | Exposure route  | Dose          |                | Species | Source              | Method             |  |  |
| 64742-54-7 | Distillates (petroleum),  | hydrotreated  | d heavy paraff | inic    |                     |                    |  |  |
|            | oral  | LD50<br>mg/kg | > 5000         | Rat     | Study report (1982) | OECD Guideline 401 |  |  |
|            | dermal  | LD50<br>mg/kg | > 5000         | Rabbit  | Study report (1982) | OECD Guideline 402 |  |  |
|            | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) |               |                |         |                     |                    |  |  |
|            | oral  | LD50<br>mg/kg | > 2000         | Rat     | Study report (1995) | OECD Guideline 401 |  |  |
|            | dermal  | LD50<br>mg/kg | > 2000         | Rabbit  |                     |                    |  |  |

#### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

# Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

according to UK REACH Regulation

# **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 8 of 11

# Aspiration hazard

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards

## Endocrine disrupting properties

not applicable

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met. No data available

Mixture not tested.

| CAS No  | Chemical name               |  |          |           |                               |   |   |  |  |
|---|-----------------------------|--|----------|-----------|-------------------------------|---|---|--|--|
|   | Aquatic toxicity            | Dose   |          | [h]   [d] | Species                       | Source                                  | Method  |  |  |
| 64742-54-7  | Distillates (petroleum), hy | Distillates (petroleum), hydrotreated heavy paraffinic |          |           |                               |   |   |  |  |
|   | Acute fish toxicity         | LL50<br>mg/l   | > 100    | 96 h      | Pimephales promelas           | Study report<br>(1995)                  | OECD Guideline<br>203                         |  |  |
|   | Acute algae toxicity        | ErC50<br>mg/l  | >100     | 72 h      |                               |   |   |  |  |
|   | Fish toxicity               | NOEC<br>mg/l   | >= 1000  | 14 d      | Oncorhynchus mykiss           | CONCAWE,<br>Brussels, Belgium<br>(2010) | The aquatic<br>toxicity was<br>estimated by a |  |  |
| Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosp amines, C12-14-alkyl (branched) |                             |  |          |           | oric acid with phosphorus     | s oxide, propylene oxi                  | de and  |  |  |
|   | Acute fish toxicity         | LL50<br>mg/l   | ca. 24   | 96 h      | Oncorhynchus mykiss           | REACh<br>Registration<br>Dossier        | OECD Guideline<br>203                         |  |  |
|   | Acute algae toxicity        | ErC50  | 6,4 mg/l | 96 h      | Raphidocelis<br>subcapitata   | REACh<br>Registration<br>Dossier        | OECD Guideline<br>201                         |  |  |
|   | Acute crustacea toxicity    | EL50<br>mg/l   | ca. 91,4 | 48 h      | Daphnia magna                 | REACh<br>Registration<br>Dossier        | OECD Guideline<br>202                         |  |  |
|   | Acute bacteria toxicity     | EC50<br>mg/l()   | ca. 2433 | 3 h       | activated sludge,<br>domestic | REACh<br>Registration<br>Dossier        | OECD Guideline<br>209                         |  |  |

# 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

## 12.3. Bioaccumulative potential

### No data available

#### Partition coefficient n-octanol/water

| CAS No | Chemical name  | Log Pow |
|--------|--|---------|
|        | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide,<br>propylene oxide and amines, C12-14-alkyl (branched) | < 0,3   |

BCF

| CAS No | Chemical name  | BCF | Species              | Source               |
|--------|--|-----|----------------------|----------------------|
|        | Reaction products of<br>bis(4-methylpentan-2-yl)dithiophosphori<br>c acid with phosphorus oxide,<br>propylene oxide and amines,<br>C12-14-alkyl (branched) | 436 | Onchorhynchus mykiss | REACh Registration D |

according to UK REACH Regulation

## **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 9 of 11

### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

#### No data available

### Further information

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

#### List of Wastes Code - residues/unused products

130110 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; mineral based non-chlorinated hydraulic oils; hazardous waste

#### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

| <u>14.1. UN number or ID number:</u>     | -  |
|--|----|
| 14.2. UN proper shipping name:           | -  |
| 14.3. Transport hazard class(es):        | -  |
| 14.4. Packing group:                     | -  |
| Inland waterways transport (ADN)         |    |
| 14.1. UN number or ID number:            | -  |
| 14.2. UN proper shipping name:           | -  |
| 14.3. Transport hazard class(es):        | -  |
| 14.4. Packing group:                     | -  |
| Marine transport (IMDG)                  |    |
| 14.1. UN number or ID number:            | -  |
| 14.2. UN proper shipping name:           | -  |
| 14.3. Transport hazard class(es):        | -  |
| 14.4. Packing group:                     | -  |
| Air transport (ICAO-TI/IATA-DGR)         |    |
| 14.1. UN number or ID number:            | -  |
| 14.2. UN proper shipping name:           | -  |
| <u>14.3. Transport hazard class(es):</u> | -  |
| 14.4. Packing group:                     | -  |
| 14.5. Environmental hazards              |    |
| ENVIRONMENTALLY HAZARDOUS:               | No |
| 14.6. Special precautions for user       |    |

according to UK REACH Regulation

## **ADDINOL Hydraulic Oil HVLPD 68**

Revision date: 21.01.2025

Product code: 735001

Page 10 of 11

### Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

### Other applicable information

No dangerous good in sense of these transport regulations.

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,12.

## Abbreviations and acronyms

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Relevant H and EUH statements (number and full text)

| H302 | Harmful if swallowed.                         |
|------|---|
| H304 | May be fatal if swallowed and enters airways. |
| H317 | May cause an allergic skin reaction.          |

according to UK REACH Regulation

# **ADDINOL Hydraulic Oil HVLPD 68**

|                                     | Revision date: 21.01.2025 | Product code: 735001                            | Page 11 of 11 |
|-------------------------------------|---------------------------|---|---------------|
| H319 Causes serious eye irritation. |                           |   |               |
|                                     | H/11                      | Toxic to aquatic life with long lasting effects |               |

H411Toxic to aquatic life with long lasting effects.EUH210Safety data sheet available on request.

### Further Information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)